6 - 23

4-<u>041381</u>

15-137-00542-00-00

972

TO: API number: 15- - 5-4-61 STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING \underline{SWSWSE} /4 SEC. $\underline{25}$, $\underline{05}$ S, $\underline{21}$ W 200 COLORADO DERBY BUILDING 330 ___ feet from S section line WICHITA, KANSAS 67202 2310 ____ feet from E section line Operator license# 5447 Lease_Finnigan 'A' well # 4 Operator: OXY USA, Inc. County Norton Address: 110 S. Main __ Well total depth <u>3665</u> feet #800 Conductor Pipe: 0 inch @ 0 feet Wichita, Kansas 67202 Surface pipe 8 5/8 Inch @ 238 feet W/250 sx.cmt. Aband. oil well <u>X</u>, Gas well ___, Input well ___, SWD ___, D & A ___ Plugging contractor: B.J. Titan License# -Address: <u>Hays</u>, <u>Kansas</u> 67601 Company to plug at: Hour: 8:00A.M. Day: 23 Month: June Year: 92 Plugging proposal received from: J.D. Hininger Company: OXY USA, Inc. Phone: 913-434-7681 Were: ____ 5 1/2" casing set @ 3662'- 3665' w/150 sx. Perf. @ 3662'- 3665' D.V. @ 1859' W/400 sx. T.O.F. 1700'. Ordered 300 sxs. 60/40 pozmix - 10% gel. with 1/4# F.C. plus 500# hulls. Plugging Proposal Received by: <u>Dennis L. Hamel</u> Plugging operations attended by agent? All[X], Part[], None[Completed: Hour: 1:20P.M., Day: 23 , Month: June , Year: 92 Actual plugging report: Hooked-up to 5 1/2" casing. Pumped in 210 sx. cement with 250# hulls in cement. Max. 1500#. S.I. 1100#. Hooked-up to 8 5/8" casing, pressured up to 650#. STATE CORPOL Remarks: Condition of casing(in hole):GOOD X BAD Anhy.plug:YES X NO Bottom plug(in place):YES X ,CALC X ,NO Dakota plug:YES X ,NO Plugged through TUBING , CASING X . Elevation: not[] observe the plugging. (agent) Form CP-2/3