STATE OF KANSAS STATE CORPORATION COMMISSION 200 Colorado Derby Bldg. Wichita, Kansas 67202

18-137-20206-00-00

WELL PLUGGING RECORD

Make Required Affidavit	COUNTY	Norton		SEC.	9 TWP. 5S	RGE 22W E/W
	Location a			: footage f 1/4 NE/4	rom lines:	
	Lease Owne	er Humm	on Corp	oration		
	Lease Name		Ve	ernon	Well	No. 1
					Wichita, Kar	
	Character	of Well (Complet	ed as Oil,	Gas or Dry H	Hole): D & A
	Date Well	Completed		Mild - Mill and Market - Armen and Common armen data of the Santon and Armen	October	22, 1981
	Applicatio	n for plu	ıgging f	iled	October	23, 1981
All processing and the second section of the section of the second section of the section of the second section of the	Plugging c	ommenced_		-	October	23, 1981
	Plugging c				October	
of and morte are interested and area. I state the support was an arrange of the support and area and an area and an area and area.	Reason for	abandonn	ent of	well or pr	oducing forma	ntion
Locate Well correctly on above					D & A	
Section Platt.	Was permis	sion obta	ined fr	om the Con	servation Div	vision or it's
	Agent's be	fore plug	ging wa	is commence	ed? <u>Yes</u>	
Name of Conservation Ager	nt who superv	ised plug	ging of	this well	Gil Balthaz	or
Producing formation		Depth to	top	bott	comT.	D. 3,580'
Show depth and thickness	of all water	, oil and	gas fo	rmations.	·	
OIL, GAS OR WATER RECORDS	5					Casing Record
Formation	Content	From	To	Size	Put in	Pulled Out
				8 5/8"	268.03'	
				l .		1
						1
Describe in detail the fluid was placed and the or other plugs were used,	method or me	thods use	d in in	troducing	it into the h	old. If cement
fluid was placed and the or other plugs were used,	method or me , state the c ch plug set	thods use haracter Plugged v Bridge P 10 sx cer	d in in of same well @	e and depth 900' w/70 260' w/40 0' to sur	it into the hamplaced, from sx cement sx cement face w/10 sx	old. If cement
fluid was placed and the or other plugs were used,	method or me , state the c ch plug set	thods use haracter Plugged v Bridge P 10 sx cer	d in in of same well @	troducing and depth 900' w/70 260' w/40 0' to sur	it into the hamplaced, from sx cement sx cement face w/10 sx	old. If cement
fluid was placed and the or other plugs were used,	method or me , state the c ch plug set	thods use haracter Plugged v Bridge P 10 sx cer	d in in of same well @	e and depth 900' w/70 260' w/40 0' to sur	it into the hamplaced, from sx cement sx cement face w/10 sx	old. If cement
fluid was placed and the or other plugs were used,	method or me , state the c ch plug set	thods use haracter Plugged v Bridge P 10 sx cer	d in in of same well @	e and depth 900' w/70 260' w/40 0' to sur	it into the hamplaced, from sx cement sx cement face w/10 sx	old. If cement
fluid was placed and the or other plugs were used, to	method or me state the control plug set	thods use haracter Plugged v Bridge P 10 sx cer 50-50 Pox	d in in of same well @ @ lug @ 4 ment in zmix, 4 sary, uing Com	e and depth 900' w/70 260' w/40 0' to sur rathole % Gel, 3%	it into the hamplaced, from sx cement sx cement face w/10 sx C.C.	old. If cement
fluid was placed and the or other plugs were used, to	method or me state the c ch plug set description cor	thods use haracter Plugged v Bridge P 10 sx cer 50-50 Poz	d in in of same well @ @ lug @ 4 ment in zmix, 4 sary, uing Comng, Wic	e and depth 900' w/70 260' w/40 0' to sur rathole % Gel, 3% see BACK of pany hita, Kans	it into the half placed, from sx cement sx cement face w/10 sx C.C.	old. If cement feet cement
fluid was placed and the or other plugs were used, to	method or me state the c ch plug set. description cor Red Tig 1720 KS COUNTY OF ing first dul atters herein	thods use haracter Plugged v Bridge P 10 sx cer 50-50 Poz is neces ger Drill: B Buildin Sedgw. (employ y sworn o	d in in of same well @ @ lug @ 4 ment in zmix, 4 sary, uing Comng, Wick ee of ment in oath, d and t	stroducing and depth 900' w/70 260' w/40 0' to surrathole % Gel, 3% as BACK of pany hita, Kans,ss. www.xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	it into the hamplaced, from sx cement sx cement face w/10 sx C.C. this sheet) sas 67202 contractor concexxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	cement cement cement cement cement
fluid was placed and the or other plugs were used, to	method or me state the c ch plug set. description cor Red Tig 1720 KS COUNTY OF ing first dul atters herein	thods use haracter Plugged v Bridge P 10 sx cer 50-50 Poz is neces ger Drill: B Buildin Sedgw. (employ y sworn o	d in in of same well @ @ lug @ 4 ment in zmix, 4 sary, uing Comng, Wick ee of ment in oath, d and to So hel	stroducing and depth 900' w/70 260' w/40 0' to sure rathole % Gel, 3% as BACK of pany hita, Kans says: The log of p me God.	it into the half placed, from sx cement sx cement face w/10 sx C.C. this sheet) sas 67202 contractor contractor at I have known the above-des	cement cement
fluid was placed and the or other plugs were used, to	method or me state the control of the plug set. I description or Red Tige 1720 KS COUNTY OF the control of th	thods use haracter Plugged v Bridge P 10 sx cer 50-50 Poz is neces ger Drill: B Buildin Sedgw (employ y sworn of contained correct.	d in in of same well @ @ lug @ 4 ment in zmix, 4 sary, uing Comng, Wick ee of ment in oath, d and to So hel	stroducing and depth 900' w/70 260' w/40 0' to sure rathole % Gel, 3% as BACK of pany hita, Kans says: The log of p me God. 1720 F	it into the hamplaced, from sx cement sx cement face w/10 sx C.C. this sheet) sas 67202 contractor contractor fact I have known the above-des	cement cement cement cement cement cement wichita, Ks. s)
fluid was placed and the or other plugs were used, to	method or me state the control of the plug set. I description or Red Tige 1720 KS COUNTY OF the control of th	thods use haracter Plugged v Bridge P 10 sx cer 50-50 Poz is neces ger Drill: B Buildin Sedgw (employ y sworn of contained correct.	d in in of same well @ @ lug @ 4 ment in zmix, 4 sary, u ing Coma, Wick ee of sen oath, d and t So hel (Sign	stroducing and depth 900' w/70 260' w/40 0' to sure rathole % Gel, 3% as BACK of pany hita, Kans says: The log of p me God. ature)	it into the ham placed, from sx cement sx cement face w/10 sx c.C. this sheet) sas 67202 contractor contractor fact I have known the above-destinated factor (Address October ,	cement cement cement cement the wilding of the wilding of the cribed well as Wichita, Ks. s) 19 81.
fluid was placed and the or other plugs were used, to	method or me state the control of the plug set. I description or Red Tige 1720 KS COUNTY OF the control of th	thods use haracter Plugged v Bridge P 10 sx cer 50-50 Poz is neces ger Drill: B Buildin Sedgw (employ y sworn of contained correct.	d in in of same well @ @ lug @ 4 ment in zmix, 4 sary, u ing Coma, Wick ee of sen oath, d and t So hel (Sign	stroducing and depth 900' w/70 260' w/40 0' to sure rathole % Gel, 3% as BACK of pany hita, Kans says: The log of p me God. ature)	it into the ham placed, from sx cement sx cement face w/10 sx c.C. this sheet) sas 67202 contractor contractor fact I have known the above-destinated factor (Address October ,	cement cement cement cement wichita, Ks. s) 19 81. ary Public.

JOYCE A. BAER State of Kansas ly Appt. Exp. 10-18-84

OCT 30 1461