4-031984 9-29

TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API number: 15-137-20,131 SW NE SE /4 SEC. 12 , 05 S, 22 W 1650 feet from S section line 990 feet from E section line		
Operator license#_5252_	Lease Hockman well # 1		
Operator: R.P. Nixon Operations, Inc.	County Norton		
Address: 207 West 12th Street Hays, Kansas 67601-3898	Well total depth <u>3480</u> feet Conductor Pipe: <u>0</u> inch @ <u>0</u> feet Surface pipe 8 5/8 Inch @ <u>257</u> feet		
Aband. oil well <u>X</u> , Gas well, Inpu	ut well, SWD, D & A		
Plugging contractor: <u>Jay-Lan Corporation</u> License# <u>5128</u>			
Address: Hays, Kansas 67601			
Company to plug at: Hour: A.M. Day:	29 Month: September Year: 94		
Plugging proposal received from: Paul Nixon Company: R.P. Nixon Operations, Inc. Phone:			
		Plugging Proposal Received by: <u>Carl Goo</u> Plugging operations attended by agent?	All[X], Part[], None[]
Completed: Hour: 10:31A.M, Day: 29, Mor	nth: <u>September</u> , Year: <u>94</u>		
Actual plugging report: 8 5/8" set @ 257' w/200 sxs. 4 1/2" set at 3476' w/125 sxs. O.H. sand back - ran tubing to 1610'. Pumped 50 sxs. cement with 100# hulls. Pulled to 610'. Pumped 100 sxs. cement w/100# hulls to circulate cement. Pulled tubing - squeezed 4 1/2" with total 200 sxs. cement blend with 200# hulls to Max. P.S.I. 400#. Close in P.S.I. 400#. Test 8 5/8" to 500# cement at surface from old squeeze. Plug complete.			
Remarks: Condition of casing(in hole):GOOD X BABOTTOM plug(in place):YES X ,CALC Plugged through TUBING , CASING X I did[X] / did not[] observe the pl	,NODakota plug:YES >,NO		
9-29 DEC 12 1994	Adjerson		