

5-3

4-032059

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 S. MARKET, ROOM #2078
WICHITA, KANSAS 67202

API number: 15-137-20,057-A00-03
NE SE SE /4 SEC. 11, 05 S, 22 W
990 feet from S section line
330 feet from E section line

Operator license# 5252 Lease Stenger well # A-4

Operator: R.P. Nixon Operations County Norton

Address: 207 W. 12th Street Well total depth 3597 ^{116.90} feet
Hays, Kansas 67601 Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 211 feet

Aband. oil well X, Gas well , Input well , SWD , D & A

Plugging contractor: Allied Cement Company License#

Address: Hays, Kansas 67601

Company to plug at: Hour: P.M. Day: 3 Month: May Year: 95

Plugging proposal received from: Paul Nixon

Company: R.P. Nixon Operations Phone:

Were: Order 225 sxs. 60/40 pozmix - 10% gel - 7 sxs. gel - 400# hulls.

STATE CORPORATION COMMISSION
MAY 1 9 1995
CONSERVATION DIVISION
WICHITA, KANSAS
519-95

Plugging Proposal Received by: Carl Goodrow
Plugging operations attended by agent? All[X], Part[], None[]

Completed: Hour: 4:30P.M., Day: 3, Month: May, Year: 95

Actual plugging report: 8 5/8" set @ 211' w/150 sxs. cwc. 4 1/2" set at 3592' w/125 sxs. Cemented hole in casing at 1200' w/210 sxs. Squeezed 8 5/8" w/50 sxs. cement blend. T.D. 300#. Close to 150#. Squeezed 4 1/2" w/25 sxs. cement blend with 200# hulls - followed by 7 sxs. gel - followed by 150 sxs. cement blend w/200# hulls to Max. P.S.I. 1200#. Close in 300#. Critical area control shots at 990' - 1740'.

Remarks:
Condition of casing(in hole): GOOD X BAD Any plug: YES X NO
Bottom plug(in place): YES , CALC X, NO Dakota plug: YES X, NO
Plugged through TUBING , CASING X. Elevation: GL

I did[X] / did not[] observe the plugging. Carl Goodrow
(agent)

INVOICED
DATE 5-24-95
INV. NO. 42890

(Handwritten initials)