

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-051-22099-00-00
Spot: NENWNW Sec/Twnshp/Rge: 25-15S-18W
4950 feet from S Section Line, 4370 feet from E Section Line
Lease Name: FRED WOLF LEASE Well #: 1
County: ELLIS Total Vertical Depth: 3500 feet

Operator License No.: 9860
Op Name: CASTLE RESOURCES, INC.
Address: BOX 87
SCHOENCHEN, KS 67667

CIBP Size: feet: 3520
PROD Size: 4.5 feet: 3818 275 SX CMT
SURF Size: 8.625 feet: 1109 450 SX CMT

\$ 113⁷⁵

Well Type: SWD UIC Docket No: D20260.0 Date/Time to Plug: 12/20/2004 2:00 PM
Plug Co. License No.: 31925 Plug Co. Name: QUALITY WELL SERVICE, INC.
Proposal Rcvd. from: JOE MAES Company: QUALITY WELL SERVICE, INC. Phone: (620) 727-3410

Proposed Plugging Method: Ordered out 210 sxs 60/40 pozmix - 10% gel - 500# hulls.

Plugging Proposal Received By: JAY PFEIFER WitnessType: COMPLETE (100%)
Date/Time Plugging Completed: 12/20/2004 6:00 PM KCC Agent: JAY PFEIFER

Actual Plugging Report:

Sanded off casing to 3410' and topped with 5 sxs cement using a dump bailer.
Cut casing loose at 1700'.
Pulled up to 1600' - mixed and pumped 80 sxs cement with 300# hulls.
Pulled up to 1100' - spotted 40 sxs cement with 100# hulls.
Pulled up to 550' - spotted 40 sxs cement with 100# hulls.
Pulled up to 200' - circulated cement with 50 sxs cement.
POOH. Hole full of cement.

Perfs:

Top	Bot	Thru	Comments
3484	3488		

RECEIVED
DEC 30 2004
KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: CSG

District: 04

Signed

Jay Pfeifer

(TECHNICIAN)

INVOICED

DATE

1-3-05

INV. NO.

2005061027

Form CP-2/3

DEC 27 2004

D L WISWELL OPERATIONS
 RT #1 BOX 14 #1 FRED WOLF LEASE 25-15-18W
 HAYS, KS 67601 NE NW NW
 CONTR BUFFALO DRILLING COMPANY CTY ELLIS

GEOL JIM BISHOP FIELD BIELMAN

E 1948 KB CM 11/21/80 CARD ISSUED 2/26/81 IP P 20 BOPD, NW
 1943 GL

+	+	+
+	+	+
+	+	+

API 15-051-22,099

DUAL COMP LANS 3456-62
 (NEW PAY) SWDW
 GR WSH OH 3818-90

SMP	TOPS	DEPTH	DATUM
ANH		1096	+ 852
B ANH		1138	+ 810
TOP		2905	- 957
TOR		3212	-1264
LANS		3242	-1294
LANS F		3306	-1358
LANS H		3370	-1422
LANS I		3394	-1446
LANS J		3409	-1461
LANS K		3435	-1487
LANS L		3453	-1505
B KC		3475	-1527
CONG		3488	-1540
ARB DOL		3550	-1602
REAG SD		3760	-1812
GR WSH		3793	-1845

8-5/8" 1109/450sx, 4 1/2" 3818/275sx
 DST (1) 324J-330J (LANS A,B,C,D)/
 60-60-60-60, REC 5' O&GCM, FREE
 O ON TOP OF TOOL, SIP 650-118#,
 FP 59-59/59-59#
 DST (2) 3295-3350 (LKC F,G)/60-60-60-60,
 REC 5' O&GCM, SIP 354-118#, FP 59-
 59/59-59#
 DST (3) 3398-3473 (LKC J,K,L W/STR PKR)/
 780' GIP, REC 120' HG&OCM, (42%
 O, 30% G, 28% M), SIP 436-545#, FP
 54-54/76-87#
 MICT - CO, PF (LANS) 3456-62, AC 500 G
 (15%), SWB LD W/SO, RE-AC 2000 G (15%),
 SWB LD W/SO, POP, P 20 BOPD, NW W/TR
 G, DUAL COMP, SWDW - GR WSH OH 3818-90
 RTD 3890-1942

INDEPENDENT OIL & GAS SERVICE
 WICHITA, KANSAS