## 12-16 4-<u>041426</u>

TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API number: 15-163-21,280  70'E.of  C W2 NW
Operator license#_5266_	Lease Hansen Foundation well # 2
Operator: K & E Drilling, Inc.	
Address: 100 S. Main Suite 300 Wichita, Kansas 67202	Well total depth 3607 feet //7. 2 Conductor Pipe: 0 inch 0 0 feet Surface pipe 8 5/8 Inch 0 286 feet w/190 sx.
Aband. oil well $\underline{\mathbf{x}}$ , Gas well $\underline{}$ , In	out well, SWD, D & A
Plugging contractor: Allied Cementing, Inc. License#	
Address: Russell, Kansas 67665	
Company to plug at: Hour:8:30A.M. Day: 16 Month: December Year: 92	
Plugging proposal received from: Al Hammersmith	
Company: K & E Drilling, Inc.	Phone:
Anhy Perf. @ 1725'. Dakota @ 1030 Order 400 sxs. 65/35 pozmix - 8% gel.	with 1/4# F.C. plus 500# holds.  AANSAS CORPORATION COMMISSION
	DEC 2 P, ICU2
Plugging Proposal Received by: <u>Denna</u> Plugging operations attended by agent	isL. Hamel $\frac{1}{2}$
Completed: Hour: 2:30P.M., Day: 16, Mo	onth: <u>December</u> , Year: <u>92</u>
Actual plugging report: R.I.H. with tubing to 2450' spot 75 sx. cement.  Pull tubing to 1450' spot 85 sx. cement to circulate cement at surface.  Pull balance of tubing. Hooked-up to 4 1/2" casing. Squeeze 90 sx.  cement with 300# hulls. Max. 700#. S.I.P 700#. Hooked-up to 8 5/8"  S.P. and pump 100 sx. cement with 200# hulls. Max. 750#. S.I.P. 500#.	
Remarks: Condition of casing(in hole):GOOD Bottom plug(in place):YES x ,CALC : Plugged through TUBING x , CASING  I did(x0] Cdrd not[ ] observe the process of the plugged in the plugged	K,NODakota plug:YES_X,NO Elevation:GL
JATE 127 127	(agent)
MV. NO. 3	Form CP-2/3