

6 070396

AP# NUMBER 15-162-22,658-00-00

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION NE-SW-SW, SEC. 16, T. 6 S, R. 20 W
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

990 feet from S section line
4290 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 8925
Operator: Liberty Operations & Comp.
Name & Address: 308 West Mill
Plumville, Mo. 67663
David Comeau

Lease Name Geyer Well # 3
County 200 No. 124.48
Well Total Depth 3820 feet
Conductor Pipe: Size 0 feet
Surface Casing: Size 8 5/8" feet 259 ✓

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A

Other well as hereinafter indicated Tag # 256

Plugging Contractor Pioneer Drilling Co. Inc License Number 5665

Address Plumville Mo

Company to plug at: Hour: 6:00 PM Day: 25th Month: Sept Year: 19 85

Plugging proposal received from Tom Alm

(company name) Pioneer Drilling Co (phone) 913-434-4686

were: 8 5/8" - 259' CUI #166 2 1/2" 60' 140 Foamix Gel - 2 1/2" 30% - By Allied

Order 245 6 1/2" 60' 140 Foamix Gel - co-cl. - 2 1/2" 30% - 2 1/2" 30% and 8 5/8" Plug

spot with Drill Stem, Recondition well (viscosity) Heavy Mud Between all Plugs

some Circulation Problems, tubular @ 3710' E.L.V. 2221, tubular

@ 1840' E.L.V., mud condition 48 viscosity, 9.3 weight, 9.2 water

Loss, Plugging Proposal Received by Marvion Schmidt
DOIC (TECHNICIAN)

Plugging Operations attended by Agent: All _____ Part _____ None

Operations Completed: Hour: 6:00 PM Day: 25 Month: Sept Year: 19 85

ACTUAL PLUGGING REPORT Ordered 245 6 1/2" 60' 140 Foamix Gel - co-cl. - 2 1/2" 30% - 2 1/2" 30% - 8 5/8" Plug

Spotted with Drill Stem, Reconditioned Hole, Heavy Mud Between all Plugs

Pioneer Drilling Spotted 150' 60' 140 Poz. Salt @ 1800' E.L.V. Had Lost Circulation.

Pioneer Drilling Had Regained Circulation Before they Spotted Plug.

1st Plug @ 3660' 125' 60' 140 Poz. Salt @ 1850' E.L.V. 1 1/2" 30% - 2 1/2" 30% - 8 5/8" Plug

3rd Plug @ 1120' E.L.V. / 100' 60' 140 Poz. Salt @ 1850' E.L.V. 1 1/2" 30% - 2 1/2" 30% - 8 5/8" Plug

Remarks 6th Plug null's - Plug @ 40' E.L.V. 10' 60' 140 Poz. Salt @ 1850' E.L.V. 1 1/2" 30% - 2 1/2" 30% - 8 5/8" Plug

of additional description is necessary, use BACK of this form.)
Cemented By Allied
observe this plugging. Dale Bathz. made a follow up on the signed Marvion Schmidt (TECHNICIAN)

INVOICED
DATE 10-16-85
INV. NO. 10605

10-1585 CONSERVATION DIVISION
Wichita, Kansas