

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-30223-00-00
Spot: SENESW Sec/Twnshp/Rge: 8-10S-17W
1650 feet from S Section Line, 2970 feet from E Section Line
Lease Name: PLANTE B Well #: 2
County: ROOKS Total Vertical Depth: 3575 feet

Operator License No.: 5552
Op Name: GORE OIL COMPANY
Address: 202 SOUTH ST. FRANCIS PO BOX 2757
WICHITA, KS 67201

SURF Size: 8.625 feet: 152
SURF Size: 4.5 feet: 3575 w/275 sxs cmt

#116¹⁹

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 03/01/2005 1:00 PM
Plug Co. License No.: 32382 Plug Co. Name: SWIFT SERVICES, INC.
Proposal Rcvd. from: LENNY DINKEL Company: GORE OIL COMPANY Phone: (785) 289-1928

Proposed Plugging Method: Ordered out 250 sxs Swift Multi-Density cement with 500# hulls.
TOC 2600'. Top of tubing 1028'.
Removed all rods and pump - unable to fish tubing - 1028' to 3526'.

Plugging Proposal Received By: RICHARD WILLIAMS WitnessType: COMPLETE (100%)
Date/Time Plugging Completed: 03/01/2005 4:00 PM KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

Ran tubing to 1029'. Swift pumped 65 sxs Swift Multi-Density neat - circulated cement.
PTOH. Swift pumped 130 sxs SMD with 500# hulls down 4 1/2" casing.
Max. P.S.I. 500#.
Hooked up to backside. Swift pumped 25 sxs SMD.
Max. P.S.I. 300#. S.I.P. 150#.

Perfs:

Top	Bot	Thru	Comments
3432	3526		

RECEIVED
MAR 14 2005
KCC WICHITA

Remarks: SWIFT SERVICES, INC.

Plugged through: TBG

District: 04

Signed Richard Williams
(TECHNICIAN)

INVOICED


DATE 3-14-05

INV. NO. 2005061272

MAR 04 2005

NO. 100

11-63 Map No. _____
 OPER DAVIS BROS.-TRANSIT CORP.
 TULSA, OKLA.
 WELL #2 PLANTE 'B'
 CONTR TRANSIT CORP.
 FIELD EXT - PLAINVILLE FIELD (LAN)
 I.P. CO P 75 BOPD + 15 BSWPD
 LAN 3432-3526



S-T-R 8-10S-17W
 SPOT SE NE SW
 CO ROOKS, KS.
 ELEV 2098 KB

SPL:

ANH	1376 + 722
B/ANH	1476 + 622
TOP	3032 - 934
HB	3255 - 1157
TOR	3270 - 1172
LAN A	3295 - 1197
B/ "	3299 - 1201
LAN B	3329 - 1231
B/ "	3332 - 1234
LAN D	3353 - 1255
B/ "	3368 - 1270
LAN F	3376 - 1278
LAN G	3396 - 2098
B/ "	3404 - 1306
LAN H	3430 - 1332
B/ "	3450 - 1352
LAN I	3456 - 1358
B/ "	3468 - 1370
LAN J	3472 - 1374
B/ "	3489 - 1391
LAN K	3497 - 1399
B/ "	3513 - 1415

SPUD 10-6-66 8 5/8" 152 W/100 SX GEOL - JACK COLE
 NO DST'S, RTD 3577, NO LOG, 5 1/2" 3575 W/275 SX
 CO 3550, PF 12/3499-3502, 16/3504-08, 24/3520-26 (LAN)
 500A + 3500 REG A, § LD, § 9 BFPH (65% OIL) 4 HRS, PB 3490,
 PF 40/3457-67, 24/3476-82 (LAN) 3200A, § LD, § 8 BFPH (55%
 OIL) 4 HRS, PB 3450, PF 20/3432-37, 16/3442-46 (LAN)
 (50% OIL) 4 HRS, TSTG, CO 3550, PBTD, POP -
 CO P 75 BOPD + 15 BSWPD LAN 3432-3526 COMPLETED 11-4-66

Data Inc