

319-132

6 030667

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-065-22,299-00-00

NESE NW, SEC. 18, T. 6 S, R. 21 W

3630 feet from S section line

2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 4767

Lease Name FRAZEY Well # 3

Operator: RITCHIE EXP. INC.

County GRAHAM 109.69

Name & Address 125 N. MARKET, STE. 1000

Well Total Depth 3375 feet

WICHITA, KANSAS

Conductor Pipe: Size _____ feet

67202

Surface Casing: Size 8 5/8 feet 250' w/200sx.

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor MURFIN DRUG. CO. License Number 6033

Address WICHITA, KANSAS

Company to plug at: Hour: AM Day: 11 Month: 2 Year: 19 86

Plugging proposal received from LLOYD DELETTE

(company name) MURFIN DRUG. CO. (phone) _____

were: ORDER 190 SX. 60/40 P. 2.67 GAL 3% cc 8 5/8 W.P. ALLIED CMT. CO.

CONDITIONAL HOLE W/HEAVY MUD SPOT CMT. PLUGS W/D.P.

Plugging Proposal Received by Carl Goodrow
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 8:45AM Day: 11 Month: 2 Year: 19 86

ACTUAL PLUGGING REPORT DISPLACE CMT PLUG. W/D.P. @ 1970' w/25sx.

1150' w/100sx. + 1 Hull

250' w/40sx.

40' w/5BP. Hulls 10sx.

15sx. IN RATHOLE

PLUG COMPLETE

Remarks: ELEV 2305 ANHY 1968-99
(If additional description is necessary, use BACK of this form.)

INVOICED

DATE FEB 28 1986

INV. NO. 12778

2-11

STATE CORPORATION COMMISSION

FEB 28 1986

CONSERVATION DIVISION
Wichita, Kansas

Signed Carl Goodrow
(TECHNICIAN)

2-28-86

25
2-28-86

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 2/06/86 month day year

API Number 15- 065-22,299-00-00

OPERATOR: License # 4767
Name Ritchie Exploration, Inc.
Address 125 N. Market, Suite 1000
City/State/Zip Wichita, Kansas 67202
Contact Person Galen Babcock
Phone 316/267-4375

NE SE NW Sec. 18 Twp. 6 S, Rg. 21
3630
2970
Ft. from South Line of Section
Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 6033
Name Murfin Drilling Co.
City/State Wichita, Kansas

Nearest lease or unit boundary line 330 feet
County Graham
Lease Name Frazey Well # 3
Ground surface elevation est. 2300 feet MSL

Well Drilled For: Well Class: Type Equipment:
Oil SWD Infield Mud Rotary
Gas Inj Pool Ext. Air Rotary
OWWO Expl Wildcat Cable

Domestic well within 330 feet: yes no
Municipal well within one mile: yes no
Depth to bottom of fresh water 150
Depth to bottom of usable water 1200

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

Surface pipe by Alternate: 1 2
Surface pipe planned to be set 240
Conductor pipe required
Projected Total Depth 3850 feet
Formation Arbuckle

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 2/03/86 Signature of Operator or Agent Galen Babcock Title Geologist

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 240 feet per Alt.
This Authorization Expires 2-4-86 Approved By 2-4-86

Handwritten notes: 2104 Delatt, 2-7-86

Handwritten notes: 878240, 5 p.m., 2-8-86, 2 p.m.

Handwritten notes: water well, Dale

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Handwritten signature: Comp

Table with columns for plug depth, feet depth with, and sxs of. Includes entries for 1st plug @ 3820, 2nd plug @ 1980, 3rd plug @ 1200, 4th plug @ 270, 5th plug @ 40, and (2) Rathole with 1.0 sxs.

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office after well is either plugged or production casing is cemented in.

(Call 7 a.m. to 5 p.m. workdays)

District office use only:

API #15- 065-22,299
Surface casing of feet set with sxs at 19
Alternate 1 or 2 surface pipe was used.
Alternate 2 cementing was completed @ ft. depth with 19
Hole plugged 19, agent

RECEIVED KCC-KDHE FEB 6 1986 JOINT DIST. #6 HAYS, KS

RECEIVED STATE COMMISSION FEB 28 1986