

15-163-20842-00-01

4-032080

8-22-95

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Number: ~~15-163-22,171 00 00~~

NEW
SW SW NW /4 SEC. 21, 06S, 19 W
2970 3630 feet from S section line
4950 feet from E section line
*036205
166-PC
per
H. Deines
Dist 4*

Operator license# 9002 Lease: Taylor Well # 1

Operator: Florence E. Taylor County: Rooks

Address: 812 Mimosa Lane Well total depth 3616 *117.52* feet
Manhattan, Kan 66502 Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 280 feet

Aband. oil well , Gas well , Input well , SWD , D & A

Plugging contractor: Allied Cement Company License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: P.M. Day: 22 Month: August Year: 1995

Plugging proposal received from: Cliff Taylor - Marion J. Schmidt

Company: Taylor - Kansas Corporation Commission Phone: _____

Were: Order 250 sxs 60/40 pozmix - 10% gel - 500# hulls.

RECEIVED
STATE CORPORATION COMMISSION

Plugging Proposal Received by: Carl Goodrow

Plugging operations attended by agent? All , Part , None

SEP 01 1995
09-01-1995
CONSERVATION DIVISION
WICHITA, KANSAS

Completed: Hour: 2:00 P.M., Day: 22, Month: August, Year: 1995

Actual plugging report: 8 5/8" set at 280' cwc with 180 sxs. 4 1/2" set at 3614' with NA sxs. Prod. Perf. N/A. Squeezed 1100' - 1500' with 250 sxs. Squeezed 8 5/8" with 50 sxs to Max. P.S.I. 900#. Close in P.S.I. 600#. Squeezed 4 1/2" with 200 sxs with 500# hulls mixed into Max. P.S.I. 900#. Close in P.S.I. 600#. 8 5/8" and 4 1/2" communicated and circulated cement up backside. Plug complete.

Remarks: _____
Condition of casing(in hole): GOOD _____ BAD _____ Anhy.plug: YES 1665 NO _____
Bottom plug(in place): YES _____, CALC _____, NO _____ Dakota plug: YES X, NO _____
Plugged through TUBING _____, CASING _____ Elevation: 2125 GL _____

INVOICED
I did / did not observe the plugging.
Carl Goodrow
(agent)

DATE 9-13-95
INV. NO. 43539

8-22 NOV 02 1995