State of Kansas



15-069-22466-00-00

Kansas Corporation Commission

MIKE HAYDEN GOVERNOR
KEITH R. HENLEY CHAIRMAN
RICH KOWALEWSKI COMMISSIONER
MARGALEE WRIGHT COMMISSIONER
JUDITH McCONNELL EXECUTIVE DIRECTOR
FRANK A. CARO, JR. GENERAL COUNSEL

CONSERVATION DIVISION SHARI M. FEIST, DIRECTOR 200 Colorado Derby Bldg. 202 W. 1st Street Wichita, KS 67202-1286 (316) 263-3238

October 4, 1988

Re: Davis #1
API No. 15-065-22466
NW SW NE 39-6-22W
Graham County

Ainsworth Operating Company Attn: Terry Hidy P.O. Box 1269 Colorado Springs, Colorado 80901

Dear Mr. Hidy:

We have received the ACO-1 and the bond log on the Davis #1.

This well was drilled under the rules for an Alternate II surface pipe. This rule, KAR 82-3-106 (b)(2)(B)(i), states that the production casing shall be cemented from 50 feet below the lowest usable water to the surface. This depth for this well is approximately 1150 ft.

The ACO-1 shows a top of cement at 900 ft. and the bond log stops at 2640 ft. Please submit to this office, a log showing the actual top of cement and your proposal for completing the cement work on this well.

We will expect the log and cement proposal to be submitted within 30 days of the date of this letter. You will be contacted by this office with either the approval of your proposal or how it needs to be modified to meet our approval. All field work must be scheduled through the Hays district office.

Thank you for your cooperation in this matter.

Sincerely.

Dennis Anderson

Engineer

cc: file D.O. 4

DA/1s