Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

Kansas Corporation Commission OIL & GAS CONSERVATION DIVISION

WELL PLUGGING RECORD K.A.R. 82-3-117

All blanks must be Filled

Form CP-4 December 2003 Type or Print on this Form Form must be Signed

Lease Operator: Kutter	Oil Co. Inc.				API Number:15 - 0	73-20-118 ~ 00 - 01		
Address: 303 S High Eureka, KS 67045					Lease Name: Peebles			
Phone: (620) 583 -4306 Operator License #: 32702					Well Number:			
Type of Well: (Oil, Gas D&A, SWD, ENHR, The plugging proposal was by: Mike Heffern Is ACO-1 filed? Yes Producing Formation(s): Lis Miss	Water Supply Well, Cathodia s approved on: 3-6-05 No If not, is we st All (If needed attach and Depth to Top: Depth to Top: Depth to Top:	ell log attached ther sheet) OO Bottom Bottom	#: D-27915 (If SWD (KCC District A) 17 Yes 18: 2110 T.	or ENHR) (Date) gent's Name) √ No D. 2131 D	Spot Location (QQQQ): 366 Feet from 171 Feet from Sec. 332 Twp. 25 County: Greenwood Date Well Completed:	9-28-67		
Show depth and thickness Oil, Gas or W		formations.		asina Record (Surface Conductor & Producti	(an)		
Formation	Content	From	To	Size	Put In	Pulled Out		
Miss	Oil	0	2130	5 1/2	2130	700'		
Describe in detail the mann hole. If cement or other pl Mix 7 sxs cement run shot 5 1/2 csq @	ugs were used, state the n dump bailer in hole	character of seto 2090' po	same depth pla ut 7 sxs @ 2	aced from (bott 2090	om), to (top) for each plug	nethods used in introducing it into the set.		
Name of Plugging Contract		, Inc.			License #: 32701	RECEIVED		
Address: 303 S High						APR 2 9 2005		
Name of Party Responsible State of Malone		tter Oil Co Green		, SS.		KCC WICHITA		
sworn on oath, says: That same are true and correct, LORETTA Netary Public - 1 My Appt. Expire	GULICK State of Kansas SUBSCIARB D and S	(Signature)	2035/	High Eq. Aday of My		124/09		

∠IDATED OIL WELL SERVICES, INC. 14TH STREET, CHANUTE, KS 66720 . √31-9210 OR 800-467-8676 TICKET NUMBER 2857

LOCATION EUREKA

FOREMAN STEUR Mead

TREATMENT REPORT & FIELD TICKET CEMENT

3-16-05 LUSO Peebles Greenwood CUSTOMER KUTTER Oil MAILING ADDRESS 308 5. High Greenwood TRUCK# DRIVER TRUCK# DRIVER 444 Alan 444 STrue	DATE	- CUSTOMER #	WEL	L NAME & NUM	BER	SECTION	TOWNSHIP	RANGE	COUNTY
TRUCK# DRIVER TRUCK# DRIVER AUTTOR OI TRUCK# DRIVER TRUCK# DRIVER TRUCK# DRIVER	3-10-05	1.4488	Peebles	: H	1				<u> </u>
MAILING ADDRESS 3085. High CITY EUrekA JOB TYPE PTA HOLE SIZE HOLE DEPTH CASING SIZE & WEIGHT 5 1/2 CASING DEPTH 760' DRILL PIPE TUBING DISPLACEMENT DISPLACEMENT PSI MIX PSI REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING NIX PSI RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING POST MIX PSI RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 COSING: Break Circulation 165845 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING CEMENT LEFT in CASING RATE REMARKS: Safty Meeting: Rigup To 5 1/2 CEMENT LEFT in CASING CEMENT LEFT in CASING RATE REMARKS: Safty Meeting To 1/2 REMARKS: Safty Meeting	CUSTOMER	<u> </u>			1		L	1	1000 KENWOOD
MAILING ADDRESS 3085. High CITY STATE ZIP CODE LurekA JOB TYPE PTA HOLE SIZE HOLE DEPTH CASING SIZE & WEIGHT 5'2 CASING DEPTH JOO' DRILL PIPE TUBING OTHER SLURRY WEIGHT SLURRY VOL WATER gal/sk CEMENT LEFT in CASING DISPLACEMENT DISPLACEMENT PSI MIX PSI REMARKS: Safty Meeting: Rigup To 5'2 (asing Break Circulation Mix 25ks Ge! 15 5ks 69/40 Poz mix Cement With 4% Ge! Displace With 15 bb//s Wotel. 16 5ks 69/40 Poz mix Cement With 4% Ge! Displace With 15 bb//s Wotel. 16 5ks 69/40 Poz mix Cement With 4% Ge! Displace With 15 bb//s Wotel. 16 5ks 69/40 Poz mix Cement With 4% Ge! Displace With 15 bb//s Wotel. Post of Cosing Fill Sol Complete Rig down	KUTTE	011	•			TRUCK#	DRIVER	TRUCK#	DRIVER
CITY STATE ZIP CODE Eureka XS Z7045 JOB TYPE PTA CASING DEPTH CASING SIZE & WEIGHT 5/3 DRILL PIPE TUBING OTHER SLURRY WEIGHT SLURRY VOL WATER gal/sk CEMENT LEFT in CASING DISPLACEMENT PSI MIX PSI REMARKS: Safty Meeting: Rigap To 5/3 (asing Break Circulation Mix 25ks Ge/ 18 5ks 6/40 Poz mix Cement With 4/8 Ge/ Displace With 15/4b/s woter. DISPLACE WITH 15/4b/s woter. Park Corculation 1005 RS Cement Suproce. Pall out 15/4 Post of Cosing Fill DISPLACE REMARKS. Sob Complete Rig down	MAILING ADDRE	ESS			1	2/2/21	Alon		
CITY EUREKA JOB TYPE PTA HOLE SIZE HOLE DEPTH CASING SIZE & WEIGHT 5'3 CASING DEPTH 760' DRILL PIPE TUBING OTHER SLURRY WEIGHT SLURRY VOL WATER gal/sk CEMENT LEFT IN CASING RATE REMARKS: Safty Meeting: Rig up 70 5'8 (asing Break Circulation Mix 35ks Gel 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter 18 5ks 69/40 Poz mix Cement With 4% Gel DISPLACE WITH 18 2 bbls woter With 4% Gel	308	5. High							<u> </u>
Lureka KS 67045 JOB TYPE PTA HOLE SIZE HOLE DEPTH CASING SIZE & WEIGHT 5 3 CASING DEPTH 760' DRILL PIPE TUBING OTHER SLURRY WEIGHT SLURRY VOL WATER gal/sk CEMENT LEFT in CASING DISPLACEMENT DISPLACEMENT PSI MIX PSI RATE REMARKS: Safty Meeting: Rig up to 5 % Casing. Break Circulation Mix 25ks Gel 13 5ks 640 Poz mix Cement With 4% Gel Dis Place With 15 2 bb/s Woter. WITH 4% Gel Dis Place With 15 2 bb/s Woter. DISPLACEMENT FOR MIX PSI REMARKS: Safty Meeting Rig up to 5 % Casing. Break Circulation DISPLACEMENT SUBJECT WITH 4% Gel Dis Place With 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% Gel Dis Place With 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% Gel DIS Place With 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% Gel DIS Place With 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% Gel DISPLACE WITH 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% Gel DISPLACE WITH 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s Woter. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s WOTER. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s WOTER. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s WOTER. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s WOTER. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s WOTER. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s WOTER. DISPLACEMENT SUBJECT WITH 4% GEL DISPLACE WITH 15 2 bb/s WOTER.	CITY		STATE	ZIP CODE	1		3/208		
JOB TYPE PTA HOLE SIZE HOLE DEPTH CASING SIZE & WEIGHT 5/3 CASING DEPTH 760' DRILL PIPE TUBING OTHER SLURRY WEIGHT SLURRY VOL WATER gal/sk CEMENT LEFT in CASING DISPLACEMENT DISPLACEMENT PSI MIX PSI RATE REMARKS: Safty Meeting: Rig up To 5/8 Casing. Break Circulation Mix 25/45 Gel 18 5/45 Golfford Mix Cement With 4/8 Gel Dis Place With 18/2 bhls woter. 18 5/45 Golfford Mix Gosting Rig Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Gosting Rig Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Gosting Rig Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Gosting Rig Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Gosting Rig Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Gosting Rig Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Circulation 18 5/45 Golfford Mix Psi Back up To 5/2 Cosing. Break Up To 5/2 Cosing. Break Up To 5/2 Cosing.	Eureki	A	25	67045		A paragraph		, 3,	
CASING DEPTH 760 DRILL PIPE TUBING OTHER SLURRY WEIGHT SLURRY VOL WATER gal/sk CEMENT LEFT in CASING DISPLACEMENT DISPLACEMENT PSI MIX PSI RATE REMARKS: Safty Meeting: Rig up To 5 % Casing. Break Circulation M:X 25K5 Gel 155K5 Golffo Poz mix Cement with 4% Gel Displace with 152bb/s woter. Light Tapallout Cosing Rig back up To 5 2 Cosing. Break Circulation 1605R35 Cement 265 to Suppoce. Pull out Pest of Casing. Fill 2607 Dack up. Sab Complete Rig down	-		HOLE SIZE		HOLE DEPTH	7.3 2 3 4 1 A 1	CASING SIZE & W	LIFIGHT 5名	J
SLURRY WEIGHT SLURRY VOL WATER gal/sk CEMENT LEFT in CASING DISPLACEMENT DISPLACEMENT PSI MIX PSI RATE REMARKS: Safty Meeting: Big up To 5 % Casing. Break Circulation Mix 25ks Gel 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter. 18 5ks 69/40 Poz mix Cement With 4% Gel Displace With 15 % bb/s woter.	CASING DEPTH	760'	DRILL PIPE			. /		,	*
DISPLACEMENT DISPLACEMENT PSI MIX PSI RATE REMARKS: Safty Meeting: Rig up To 5's Casing. Break Circulation Mix 25ks Gel 18 5ks Golfford Mix Cement With 4% Gel Displace With 18 2 bb/s Woter. 18 5ks Golfford Mix Cement With 4% Gel Displace With 18 2 bb/s Woter. 18 5ks Golfford Mix Cement With 4% Gel Displace With 18 2 bb/s Woter. 18 5ks Golfford Mix Cement With 4% Gel Displace With 18 2 bb/s Woter. 18 5ks Golfford Mix Cement With 4% Gel Displace With 18 2 bb/s Woter. 18 5ks Golfford Mix Cement With 4% Gel Displace With 18 2 bb/s Woter. 18 5ks Golfford Mix Cement With 4% Gel Displace With 18 2 bb/s Woter. 18 5ks Golfford Mix Psi 18	SLURRY WEIGH	T	SLURRY VOL	hy	WATER gal/sl	k			
REMARKS: Safty Meeting: Rigup To 5% Casing. Break Circulation Mix 25% Gel 18 5% 60/40 Poz mix Cement With 4% Gel Displace With 18 2661s Woter. 18 5% 60/40 Poz mix Cement With 4% Gel Displace With 18 2661s Woter. 18 5% Casing Break Circulation 18 5% Cement Best 18 Suppoce. Pull out pest of Casing Fill 20 20 Back up. Sob Complete Rig down 30 20 Complete Rig down					MIX PSI	<u> </u>	RATE		
185ks 6940 Poz min Cement With 486cl Displace With 182bbls Woter. 185ks 6940 Poz min Cement With 486cl Displace With 182bbls Woter. 185ks 6940 Poz min Cement Break Circulation 185ks 6940 Poz Min Break Circulation 185ks 6940 Poz Min Break Control of Cosing Poz Min Break Circulation 185ks 6940 Poz Min Break Cosing Break Circulation 185ks 6940 Poz Min Break Cosing Break Circulation 185ks 6940 Poz Min Break Cosing Break Circulation 185ks 6940 Poz Min Break Circulation 185ks 6940	REMARKS: 5	afty meet	and the second second					mix 2	iks Rel
Littorit To Pull out Costing Break Circulation 1605K3 Cement 100 Best 18 Suproce. Pull out 1057 of Cosing Portill Love Back up 1 506 Complete Rig down The state of the sta	155ks	60/40 Poz	m'x Cem	icht WiTh	4%60	Displace	WITH 15	Shale bin	T=1
Losses Cement Bes 18 Suproce. Pull out nest of cosing. Fill hold Bock up. 506 Complete Rig down	A CO	17 78 Du	11 GUTUGA C	Basselle	a back	10 - 2000 The 200	k care	Dr. Bar	SELECTION OF THE PROPERTY OF T
To exemplate the second of the	1005KS	Cement	285	SunFa	ce P	。ノハ · さごテニシ	rest of co		Fill
The contraction of the contract of the contrac	ろる/2 3	to Extrapo	70B	complet	R Bi	= down			
TO THE PLANT OF THE PROPERTY OF THE SERVE OF THE PARTY OF							* *		
The state of the s	10								
Thank you	- General Across Sold	register in the contraction of	mil se ist	continuitation					
			de la companya de la	Thank	You				

	T		CA 1747 1 C.	ۇد دىر ئ
ACCOUNT CODE	QUANITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
54.65 A	- 1 compression	PUMP CHARGE	335.00	
HE ARE	State	MILEAGE		7373200
1131	7155K	66/40 Por mix Cement	7.80	897.00
1118	25ks	Get in the second of the second	13.00	26.00
3 23 25 -	TO THE PLANT OF THE PARTY OF	HEADERS AND AND THE STATE OF TH	कृष अवंशिक्षात्र	
62 0 Q	ALCOHOL SPANNER OF	of the state of th	the transfer and	11 4 22 3
	The state of the s	and the action of the second o	We have a second server	ng statum
	f warder have be			
2 14 S J	कृत १९ कृत १८ के १ ८६८ १८५ ४	the process to the second of t		· · · · · · · · · · · · · · · · · · ·
at in the same of	n level in 1990 og skriver i bli værer skriver i det i d Stræmer i det	A CONTRACT OF THE STATE OF THE	RECEIVE	n
	tate state on the material		RECEIVE	U
	A COMPANY OF THE PROPERTY OF THE	THE STATE OF THE S	APR 2 9 20)5
	,		CC WICH	IITA
	,		COC WICE	H-1/A
	,		,	*
	,			
		10		
			Sub ToTal	1289.00
.]		, h	SALES TAX	55146
		. , ,	ESTIMATED	12/11-0

AUTHORIZTION Called by Tim Gulick

TITLE OWNER

TOTAL

DATE 3-10-05 /2/1/0/15