

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-163-20769-00-00
Spot: NWNWSW Sec/Twnshp/Rge: 18-7S-16W
2310 feet from S Section Line, 4950 feet from E Section Line
Lease Name: YOUNG Well #: 1
County: ROOKS Total Vertical Depth: 3270 feet

Operator License No.: 101
Op Name: KCC FEE FUND PLUG
Address: 130 S. MARKET
WICHITA, KS 67202

PROD Size: 5.5 feet: 3039 w/200 sxs cmt
SURF Size: 8.625 feet: 1117 w/450 sxs cmt

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 06/02/2005 9:00 AM
Plug Co. License No.: 3152 Plug Co. Name: POE SERVICING INC
Proposal Rcvd. from: DALE POE Company: POE SERVICING INC Phone: (785) 475-3422

Proposed Plugging Method: Ordered 350 sxs 60/40 pozmix - 10% gel - 500# hulls.
Drilled cement from 1111' to 1115' - hard metal at 1115'.
Fluid level at 300'.
Perforate 8 5/8" at 1100'.

Plugging Proposal Received By: HERB DEINES Witness Type: COMPLETE (100%)
Date/Time Plugging Completed: 06/02/2005 11:40 AM KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

Log Tech perforated at 1100'. Ran 2 3/8" tubing to 1115'.
Allied pumped 80 sxs 60/40 pozmix - 10% gel with 400# hulls - cement circulated out 5 1/2" casing.
Pulled tubing out of hole. Allied pumped 100 sxs cement with 100# hulls.
Shut in 5 1/2" casing. Hooked up to 8 5/8" and pumped 5 sxs cement.
Max. P.S.I. 500#. S.I.P. 500#.
Hooked back to 5 1/2" casing and pumped 25 sxs cement.
Max. P.S.I. 500#. S.I.P. 500#.
Total 205 sxs cement with 500# hulls down 5 1/2" casing and 5 sxs cement down 8 5/8".

Perfs:

Top	Bot	Thru	Comments
2652	2658		Topeka

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: TBG

District: 04

Signed

Richard Williams

(TECHNICIAN)

RECEIVED

JUN 15 2005

KCC WICHITA

Form CP-2/3

JUN 13 2005

