STATE OF KANSAS STATE CORPORATION COMMISSION CONSERVATION DIVISION

RECEIVED

JUL 0 7 2005

KCC WICHITA

ION DIVISION et. Room 2078

(signature) Gary M. Talbott, Agent for Operator

130 S. Market, Room 2078 Wichita, Kansas 67202

WELL PLUGGING APPLICATION FORM

(PLEASE TYPE FORM and File ONE Copy)

API #:	15-095-21974-0000	(Ider	ntifier number	of this well).	This must be	listed for wel	lls drilled sin	ce 1967; if no A	PI# was	issued, in	dicate spu
or completic	on date										1.1
WELL OPERATOR: McCoy Petroleum Corporation								KCC LIC	5003	90	
(owner/company name)								RCC LIC	LEINSE #	(operator	·'c)
V DDDECC		•	y Harrie,				CITY: V	Vichita		Operator	5)
ADDRESS: 8080 E. Central, Suite 300 STATE: Kansas ZIP CODE: 67206						CONTAC		16-636-2737			
	: Elliott GU	ir CODL	07200	WELL#:	1 20			-	20.	Dange	0
				SPOT LOCAT			30	Townshp _ COUNTY: K		Range_	9w
	E of SE NW SW FEET (in exact for	estaga) EROM						COUNTY: K	ingman		
1575 1140		-									
		, , , , , , , , , , , , , , , , , , , ,	77 051 211 12	0, 020	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						
Check One:	Oil Well		Gas Well		D&A	XX	SWE	/ENHR WELL		Docket #	!
	CONDUCTOR CASI	NG SIZE		SET AT_		CEMEN	TED WITH _			SACKS	
	SURFACE CASING SIZE 8-5/8"			SET AT 2	222' KB	CEMEN	TED WITH _	250		SACKS	
	PRODUCTION CASING SIZE None			SET AT		CEMEN	TED WITH			SACKS	
LIST (ALL) P	ERFORATIONS and BRIDG	GEPLUG SETS:								_	
EL	EVATION 1699 C	i.L.	1708	K.B.	T.D.	3997	PBTD	,	Anhydrit	e Depth	Not Know
					-	-			(Stone	e Corral F	ormation)
CONDITION	N OF WELL:	OOD	-	POOR	C	ASING LEAK		JU	JNK IN	HOLE <u>Y</u>	<u>ES</u>
PROPOSED	METHOD OF PLUGGING	i:									
	Plugged well with 35 sx	at 1300', 35 sx	at 700' , 35 :	sx at 375' and	25 sx at 60'.	Plugged rath	ole with 15 s	x and			
	mousehole with 10 sx. T	otal cement 1	55 sx 60/40 P	oz, 4% Gel. 1	Plugging com	pleted at 11:1	5pm on <i>7</i> -2-	05 by			
	Acid Services, Ticket # 1	0614. Pluggin	g orders recei	ived by Steve	Van Gieson a	t 1:00 pm on	<i>7-</i> 2-05.				
	Note: 3-bit cones left in	the hole at 399	97'.								
IS WELL LO	G ATTACHED TO THIS AI	PPLICATION A	S REQUIRED)?		Yes (Y	'ES,NO)	IS ACO-	FILED?	? (YES,NO)
	If not explain why?										
PLUGGING	OF THIS WELL WILL BE	OONE IN ACC	ORDANCE V	VITH K.S.A. 5	5-101 et. seg	. AND THE R	ULES AND F	REGULATIONS			
	TE CORPORATION COM				•						
LIST NAME	OF COMPANY REPRESEN	TATIVE AUTH	ORIZED TO	BE IN CHARC	GE OF PLUGO	GING OPERA	TIONS:				
Name	: Lanny Saloga/Gary M. Ta	lbott						Phone#: (6	520) 672	-9508	
	: P.O. Box 1006	, v, t- , , , ,	- , - , - , - , - , - , - , - , - , - ,			City: P	ratt	State: K			
		terling Drilling	Company					CC LICENSE #:		5142	- Le/
*			(company	name)							or's) /
Address	: P.O. Box 1006		, ,			City: P	ratt	State: K	ansas		6712 4
			··		8:00					_ ~	
PROPOSED	DATE AND HOUR OF PL	UGGING (If K	(nown?)	Plugged well		on July 2, 200)5. Pla	and.			
	OF THE PLUGGING FEE (K					,, -, -00		Operator	X	Agent	****
							Λ	- PO. 4.101			
DATE:	07/02/05	AUT	HORIZED O	PERATOR OR	AGENT:		()_	n J			

FORM CP-1

Rev. 03/92

RECEIVED
JUL 0 7 2005
KCC WICHITA

Sterling Drilling Company, Rig #4

Box 1006, Pratt, Kansas 67124-1006 Office Phone (620) 672-9508, Fax 672-9509

SAMPLE LOG

15-095-21974-00-00

Elliott GU 1-30

LOCATION:

75' S & 150' E of SE NW SW

Section 30 T 30s

R 9w

API:

15-095-21974-0000

Kingman County, Kansas

OWNER: McCoy Petroleum Corporation

COMMENCED:

06/22/05

CONTRACTOR: Sterling Drilling Company, Rig #4

COMPLETED:

07/02/05

TOTAL DEPTH:

DRILLER

3997 FEET

Ground Elevation:

1699

LOGGER

Not Known FEET

KB Elevation:

1708

LOG

0 - 2 FEET Top Soil

2 - 8 FEET Clay

8 - 15 FEET Sand and Gravel

15 - 180 FEET Sand and Gravel

180 - 920 FEET Redbeds

920 - 1420 FEET Shales and Salt

1420 - 3997 FEET Limestone/Shales

CASING RECORDS

Surface Casing:

Spud at 1:15 pm on 06/22/05. Drilled 12-1/4" hole to 225'. Ran 5 joints of new 23# 8-5/8" casing, tally 211.01' set at 222.01' KB. Cemented with 250 sx 60/40 Poz, 2% Gel, 3% CC, 1/4# Celloflake. Plug down at 6:30 pm on 06/22/05 by Acid Services, ticket #10704. Cement did circulate. Welded straps on bottom 2 jts, of SP, then welded collars on next 3 joints.

Plugging Information:

Plugged well with 35 sx at 1300', 35 sx at 700', 35 sx at 375' and 25 sx at 60'. Plugged rathole with 15 sx and mousehole with 10 sx. Total cement 155 sx 60/40 Poz, 4% Gel. Plugging completed at 11:15pm on 7-2-05 by Acid Services, Ticket # 10614. Plugging orders received by Steve Van Gieson at 1:00 pm on 7-2-05. Note: 3-bit cones left in the hole at 3997'.

DEVIATION SURVEYS

1/2 degree(s) at

225

feet