

FOR KCC USE:

FORM CB-1 12/93

EFFECTIVE DATE: 9.3.05

FORM MUST BE TYPED

DISTRICT # 1

FORM MUST BE SIGNED

SGA? Yes NoState of Kansas
CATHODIC PROTECTION BOREHOLE INTENT

ALL BLANKS MUST BE FILLED IN

Must be approved by the K.C.C. sixty (60) days prior to commencing well.

Expected Spud (Starting) Date 10 01 2005
month day yearSpot (Location) Q/O/O 18 33 43 East
feet from South North line of SectionOPERATOR: License # 7117130 feet from East West line of Section
(Circle directions from nearest outside corner boundaries)Name: Colorado Interstate GasIS SECTION X REGULAR IRREGULAR?Address: 2060 Briargate Pkwy. Ste 200

(Spot well on the Section Plat on Reverse Side)

City/State/Zip: Colorado Springs CO 80920County: MortonContact Person: Dave AndersonLease Name: CIG Well #: C-1072bPhone: (719) 388-5711Facility Name: El Paso CorporationGround Surface Elevation: 3652 MSLCathodic Borehole Total Depth 240 ft.Depth to Bedrock 100 ft.CONTRACTOR: License #: 32437

WATER INFORMATION:

Name: The Loftis CompanyAquifer Penetration: X None X Single X MultipleType Drilling Equipment: X Mud Rotary CableDepth to bottom of fresh water: 100 Air Rotary OtherDepth to bottom of usable water: 250Water well within one-quarter mile: yes X noPublic water supply well within one mile: yes X no

Water Source for Drilling Operations:

 well farm pond stream X otherWater Well Location: N/ADWR Permit #: N/AStandard Dimension Ratio (SDR) is = 23.66

(cathodic surface OD csg. in inches / MWT in inches = SDR)

CONSTRUCTION FEATURES

Length of Cathodic Surface (Non-Metallic) Casing 120 ft.Planned to be set: 120 of Sch. 40 PVCLength of Conductor pipe (if any?): none ft.Size of the borehole (I.D.): 12 inchesCathodic surface casing size: 6 inchesCathodic surface casing centralizers set at depths of: 40;80; 120; ; ; ; ; ; ; ; ;

Cathodic surface casing will terminate at:

 Above surface Surface Vault Below Surface VaultPitless casing adaptor will be used: N/A Yes/No at Depth ft.Anode installation depths are: 200; 210; 220; 230; ; ; ; ; ; ; ; ; ; ;

Annular space between borehole and casing will be grouted

with: X Concrete Bentonite CementX Neat cement Bentonite clayAnode vent pipe will be set at: 10 ft. above surfaceAnode conductor (backfill) material TYPE: Loresco SWDepth to BASE of Backfill installation material: 240Depth to TOP of Backfill installation material: 100

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq. It is agreed that the following minimum requirements will be met:

1. Notify the appropriate district office prior to spudding of and again before plugging well;
2. A copy of the approved notice of intent to drill shall be posted on each drilling rig;
3. The minimum amount of cathodic surface casing as specified below shall be set by grouting to the top.
4. An agreement between the operator and the district office on plugs and placement is necessary prior to plugging;
5. The appropriate district office will be notified before well is either plugged or casing is grouted in;
6. IN ALL CASES, NOTIFY DISTRICT OFFICE PRIOR TO ANY CEMENTING.

I hereby certify that the statements made herein are true and to the best of my knowledge and belief.

Date: 8/24/05 Signature of Operator or Agent: [Signature] Title: Project Manager/AgentRECEIVED
26
AUG 25 2005
KCC WICHITAFOR KCC USE:
API # 15- 129-21763-00-00 A14-3
Conductor pipe required NONE feet
Minimum cathodic surface casing required 120 feet
Approved by: RJP 8-29-05This authorization expires: 3-3-06
(This authorization void if drilling not started within
6 months of effective date.)
Spud date: Agent:

REMEMBER TO:

- File Drill Pit Application (form CDP-1) with Intent to Install;
- File Completion Form CB-2 within 30 days of spud date;
- Notify appropriate district office 48 hours prior to workover or re-entry;
- Submit plugging report (CB-4) within 30 days after plugging is completed.

Mail to: KCC - Conservation Division, 130 S. Market - Room 207B, Wichita, Kansas 67202-1286.