FOR KCC USE:	OODDEOTER FORM CB-1 12/93
EFFECTIVE DATE: 9.3.05 State of Kansas	CORRECTED FORM MUST BE TYPED FORM MUST BE SIGNED
DISTRICT # CATHODIC PROTECTION BORE	
SGA?YesXNo Must be approved by the K.C.C. sixty (60) days prior to commencing well.	
Expected Spud (Starting) Date 10 01 2005	Spot (Location) 9/9/9 .
OPERATOR: License #7117 month day year	130feet from East) West line of Section
Name: Colorado Interstate Gas	(Circle directions from nearest outside corner boundarys) IS SECTION X REGULAR IRREGULAR?
Name: Address: 2060 Briargate Pkwy, Ste 200 City/State/Zip: Colorado Springs, CO 80920	(Spot well on the Section Plat on Reverse Side) County: MOrton
Contact Person: Dave Anderson	Lease Name: CIG Well #: C-1072b
Phone: (719) 388-5711	Facility Name: El Paso Corporation GroundSurfaceElevation: 3652 MSL.
20427	Cathodic Borehole Total Depth
CONTRACTOR: License #: 32437	beptil to begin our account the second of the second our account to be
Name: The Loftis Company	MATER IMFORMATION: Aquifer Penetration: None Single Multiple
V	Depth to bottom of fresh water:100
Type Drilling Equipment: Mud Rotary Cable Air Rotary Other	Depth to bottom of usable water: 250
CONSTRUCTION FEATURES	Public water supply well within one mile: yes no
Length of Cathodic Surface (Non-Metallic) Casing	Water Source for Drilling Operations:
Planned to be set: 120 of Sch. 40 PVC ft. Length of Conductor pipe (if any?): none ft.	well farm pond stream .X. other
12	
Size of the porenole (I.U.):	DWR Permit #:
Cathodic surface casing size:	Standard Dimension Ratio (SDR) is =
80; 129	, and the same services of the
Cathodic surface casing will terminate at: Above surface Surface Vault Below Surface Vault	Annular space between borehole and casing will be grouted with: Concrete Bentonite Cement Neat cement Bentonite clay
N/A Pitless casing adaptor will be used: Yes/No at Depthft.	Anode vent pipe will be set at:10 ft. above surface
Anode installation depths are: 200 , 210 , 220 , 230	And conductor (backfill) retarial TYPE. Loresco SW
;;;;;;;;	Anode Conductor (back) (17) material fifther
	Depth to BASE of Backfill installation material: 240 Depth to TOP of Backfill installation material: 100
<u>AFFIDAVIT</u>	
The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq. It is agreed that the following minimum requirements will be met:	
1. Notify the appropriate district office prior to spudding of and again before plugging well;	
 A copy of the approved notice of intent to drill shall be posted on each drilling rig; The minimum amount of cathodic surface casing as specified below shall be set by grouting to the top. 	
An agreement between the operator and the district office on plugs and placement is necessary prior to plugging;	
 The appropriate district office will be notified before well is either plugged or casing is grouted in; IN ALL CASES, MOTIFY DISTRICT OFFICE PRIOR TO ANY CEMENTING. 	
I hereby certify that the statements made herein are true and to the best of my knowledge and belief.	
Date: 8/24/05 Signature of Operator or Agent: Title Project Manager/Agent	
FOR KCC USE: 12C	O-(1) A (4-3 INTENT EXPIRATION DATE
RECEIVED API # 15- Conductor pipe required NONE Winimum cathodic surface casing rec	feet WAS: 6 MONTHS FROM EFFECTIVE DATE 3-3-2006
Approved by: 2008-29-051	
AUG 20 This authorization expires: 3 06 2.2806	
AUG 25 AUG 25 This authorization expires: 3-3 (This authorization void if drilling to months of effective date.) Spud date: Agent:	
REMEMBER TO:	
 File Drill Pit Application (form CDP-1) with Intent to Install; 	
 File Completion Form CB-2 within 30 days of spud date; Notify appropriate district office 48 hours prior to workover or re-entry; Submit plugging report (CB-4) within 30 days after plugging is completed. 	