4-28 4-032056

TO:	API number: 15-163-21,701 -00-00
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	<u>NE SE SW</u> /4 SEC. 29 , 07 S, 17 W
130 S. MARKET, ROOM #2078	990 feet from S section line
WICHITA, KANSAS 67202	2970 feet from E section line
	Schruben
Operator license# 7011	Lease <u>K U Endowment</u> well # 1
Omerschauer Dim Oil Generatur	
Operator: Rim Oil Company	County Rooks
Address: 2101 Lincoln Drive	Well total depth 3355 feet
Hays, Kansas 67601	Conductor Pipe: 0 inch 0 0 feet
	Surface pipe 8 5/8 Inch @ 1204 feet
Aband. oil well <u>X</u> , Gas well, Input well, SWD, D & A	
Plugging contractor: Allied Cement Company License# -	
Address: Hays, Kansas 67601	
Company to plug at: Hour: A.M. Day	: 28 Month: April Year: 95
Plugging proposal received from: Myrlin Monroe	
Company: Rim Oil Company	Phone:
Were: Order 348 sxs. 60/40 pozmix - 10% gel - 500# hulls - 12 sxs. gel.	
L-K Wireline.	
Plugging Proposal Received by: <u>Carl Goodrow</u>	
Plugging operations attended by agent? All[X], Part[], None[]	
Completed: Hour: 1:15P.M., Day: 28 , Month: April , Year: 95	
Actual plugging report: 8 5/8" set at 1204' cwc. w/425 sxs. 5 1/2" set at	
3354' W/135 sxs. P.B.T.D. 3266'. Prod. perfs. 3135' - 3200'. Shots at	
1200' into 8 5/8" annulus to circulate. Squeezed 5 1/2" w/50 sxs. cement blend followed by 12 sxs. gel, followed by 198 sxs. cement blend w/500# hulls	
mixed in. 8 5/8" circulated until last 70 sxs. Ordered 100 sxs. more	
cement. Used 2 bbl 8 sxs. to Max.	P.S.I. 700#. Close in P.S.I. 500#.
Plug complete. Squeezed 8 5/8" to 500	# - would not take cement Contection
Remarks:	BAD Anhy.plug: YES X NO. Dakota plumayes y
Condition of casing (in hole):GOOD X	BADAnhy.plug:YES_X NO
Bottom plug(in place):YES,CALC_X Plugged through TUBING, CASING_	DUNCTED DIGITAL MANEE.
CADING_	a OA KON
<pre>I did[X] / did not[] observe the p</pre>	
INVOICED	(agent)
5-18-95	Form CP-2/3
DATE 5-18-45	5-15-95
W. NO. 43830	