

To: **6 041029**  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

**4-6**  
API NUMBER 15-163-21,976-00-00  
NW SE SW, SEC. 18, T. 7 S, R. 17 W/E  
\_\_\_\_\_ feet from S section line  
\_\_\_\_\_ feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 8098

Operator: Damson Oil  
Name & Address: 3311 22nd St.  
S. 228  
Woodward, Ok. 73801

Lease Name City of Stockton Well # 2-18

County \_\_\_\_\_ Rooks 109.04

Well Total Depth 3355 feet

Conductor Pipe: Size 13 3/8 feet 78' w/120 sks

Surface Casing: Size 8 5/8 feet 1258' w/450 sks

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Halliburton Cement License Number \_\_\_\_\_

Address Hays, Ks.

Company to plug at: Hour: 8:00 AM. Day: 6 Month: April Year: 19 89

Plugging proposal received from Fred Simondi

(company name) Damson Oil (phone) \_\_\_\_\_

were: 5 1/2" casing set at 3354' w/150 sks. Top perf at 3312 - 16.

Ordered 50 sks common plus ordered 300 sks 60/40 Poz 6% Gel plus 3 sks hulls.

**MAY 10 1989**  
**05-10-1989**  
COMMISSION  
CONSERVATION DIVISION  
Wichita, Kansas

Plugging Proposal Received by Dennis L. Hamel  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:10 Am Day: 6 Month: April Year: 19 89

ACTUAL PLUGGING REPORT Pumped in 5 1/2" casing 260 sks cement plus 3 sks hulls mixed  
in cement. Max 1400# S.I. 800# psi. Pumped in 8 5/8" casing 0 sks cement. Max 800#  
Annulus sq prior to plugging - 500 sks cement used.

Remarks: \_\_\_\_\_  
(If additional description is necessary, use BACK of this form.)

(If client) observe this plugging.

Signed Dennis L. Hamel  
Dennis Hamel (TECHNICIAN)

INVOICED  
DATE 5-11-89

INV. NO. 24764  
4-6

JUN 12 1989