

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-051-20544-00-00  
Spot: SENESW Sec/Twnshp/Rge: 26-11S-18W  
1650 feet from S Section Line, 2970 feet from E Section Line  
Lease Name: JACOBS-PEAVEY Well #: 2  
County: ELLIS Total Vertical Depth: 3700 feet

Operator License No.: 33263  
Op Name: BOWMAN, WILLIAM F. DBA THE BILL  
Address: 2640 W ROAD  
NATOMA, KS 67651

String	Size	Depth (ft)	Pulled (ft)	Comment
PROD	5.5	3700	0	w/150 sxs cmt
SURF	8.625	200	0	w/175 sxs cmt

#120<sup>25</sup>

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 09/09/2005 9:00 AM  
Plug Co. License No.: 32382 Plug Co. Name: SWIFT SERVICES, INC.  
Proposal Rcvd. from: BILL BOWMAN Company: THE BILL BOWMAN OIL COMPAN Phone: (785) 885-4830

Proposed  
Plugging  
Method:

Ordered 300 sxs cement and 750# hulls.

Plugging Proposal Received By: HERB DEINES Witness Type: COMPLETE (100%)  
Date/Time Plugging Completed: 09/09/2005 2:00 PM KCC Agent: ROGER MOSES

Actual Plugging Report:

Perfs:

Ran 1" tubing to 1165' - spotted 25 sxs cement.  
Pulled 1" and ran 2 3/8" tubing to 795' - circulated with 140 sxs cement and 700# hulls.  
Pulled all 2 3/8" tubing - squeezed 5 1/2" w/70 sxs cement.  
Max. P.S.I. 400#. S.I.P. 200#.  
Tied to 8 5/8" S.P. and squeezed with 35 sxs cement and 50# hulls.  
Max. P.S.I. 250#. S.I.P. 250#.  
Total of 270 sxs 60/40 pozmix - 10% gel - 750# hulls.

RECEIVED  
SEP 22 2005  
KCC WICHITA

Remarks: SWIFT SERVICES, INC. BOWMAN OIL-RIG. KELLER TANK & BOWMAN TANK-WATER

Plugged through: TBG

District: 04

Signed

Roger L Moses  
(TECHNICIAN)

INVOICED

DATE 9-22-05

TRK. NO. 2006060485

SEP 15 2005

MURFIN DRG. & VINCENT OIL  
 WICHITA, KANSAS  
 Contr. MURFIN DRILLING CO.

#2 JACOBS-PEAVEY 26-11-18W  
 SE NE SW  
 Cty. ELLIS

Geol.

Pool BEMIS-SHUTTS

E. 2109 KB Cm. 12/7/69 Cp. 4/2/70 IP P 25 B0 + WTR  
 LANS 3435-3523

API 15-051-20,544

SMP Tops	Depth	Datum
ANHY	1367	+ 742
B-ANHY	1409	+ 700
TOP	3094	- 985
HEEB	3325	-1216
TOR	3345	-1236
LANS	3369	-1260
BKC	3621	-1512
ASB	3676	-1567
	3700	-1591

Csg. 8 5/8" 200/175sx; 5 1/2" 3700/150sx  
 DST(1) 3117-3131/30", 80'M, FSIP 106#/30",  
 FP 89-89#  
 DST(2) 3275-3291/15-30-15-15, 5'M, BHP 579#  
 /30"-67#/15", FP 22-22#  
 DST(3) 3433-3615/15-30-45-30, 120'GIP, 70'  
 OCM, 868' VHO & GCM, BHP 1113#/30"-1001#  
 /30", FP 334-446#  
 PF /3614-17, /3543-47, /3525-30, /3450-53,  
 /3441-43, /3435-37, /3396-3401, 3365-68, /3372  
 74, 750 ACID 3435-3530 SWB DWN & SWB 42 BF/4HF;  
 80-98%OIL, 1250 ACID 3365-3401 SWB DWN & SWB  
 13BFPH, 82-90%OIL, 1000 ACID 3448-3523 SWB DWN  
 & SWB 30BFPH, 56%OIL, PULLED PLUGS & POP

INDEPENDENT OIL & GAS SERVICE  
 WICHITA, KANSAS

11/11/69