Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

WELL PLUGGING RECORD

Form CP-4 December 2003 Type or Print on this Form Form must be Signed All blanks must be Filled

K.A.R. 82-3-117

Lease Operator: Trans Pacific Oil Corporation					API Number: 15 - 053-20246 - 0 0 - 0 /	
Address: 100 S. Main, Suite 200, Wichita, KS 67202					Lease Name: -A. SOUKUP A-	
Phone: (316) 262 -359)6 Operator	License #:	9408	· ·	Well Number:4	
Type of Well:					Spot Location (QQQQ): SE NW _ SW _ 1648 _ Feet from North / South Section Line	
Show depth and thickness of a		ormanons.	c	asina Record (Surface Conductor & Production)	
	Content	From	То	Size	Put In Pulled Out	
		Surface	266'	8-5/8"	,	
		Surface	2964'	5-1/2"		
hole. If cement or other plugs	TTACHED SHE		ame depth pia	ced from (botto	m), to (top) for each plug set.	RECEIVED SEP 3 0 2005 KCC WICHITA
Name of Plugging Contractor: Address: P.O. Box 386,	, Claflin, KS 67	7525-0386			License #:7023	
Name of Party Responsible for	000	rans Paci		rporation		
State of Kansas	County,	Sedgwick	k	_ , \$\$.		
Gary Sharp	* *** ** ** ** *** **		- 44	_ (Employee of	Operator) or (Operator) on above-descri	ribed well, being first duly
sworn on oath, says: That I have same are true and correct, so he	help me God. (S	Signature)	say	Shay	ned, and the log of the above-described	I well is as filed, and the
	SUBSCRIBED and SW	NORN TO befo	E Jan	•	September Commission Expires:	GLENNAE, LOWE NOTARY PUBLIC STATE OF KANSAS WY Apple Fag. 12-21-07

Trans Pacific Oil Workover Report

Date:		
Lease: Soukup A	Well #:4	Legal: 16-14S-10W
KB:	Surf Csg: <u>8 5/8@ 266</u>	Prod Csg:4 ½@2964
Perfs: 2118' to 2878'	Tbg: 2 3/8"	Pkr:
Description Of Work:	P & A	

8/18/05 - Sand perfs back to 2068'

9/19/05 - MI Klima, RIH 2-7/8" notched collar on 2-3/8 tbg. Hit sand bridge at 550'. RU Shane's Wtr Serv. Circulate the short way washing tbg thru bridges from 550' to 700'. Finished running tbg to 1264'. POOH tubing.

9/20/05 - MIRU Perf Tech. RIH dump bailer and dump 4 sxs cmt on sand at 1310'. POOH bailer and RIH perf guns. Perforate 4 ½" csg at 1250', 900', and 315'. POOH guns and RDMO Perf Tech. Ticket #3552.

9/21/05 – Klima RIH 40 jts 2-3/8" tbg to 1260'. RU Allied. Allied mixed and pumped 35 sxs 60/40 pozmix with 4% gel. Pull tbg to 916'. Allied mixed and pumped 35 sxs 60/40 pozmix with 4% gel with cement circulating to surface in 4-1/2". POOH tbg. Allied pumped 48 sxs 60/40 pozmix with 4% gel down 4 $\frac{1}{2}$ " csg circulating cement through 8-5/8" to surface. No KCC rep on location. Plugged as per KCC (Duncan Berger) orders Allied cmt ticket # 21015. 118 sxs cement total.

9/26/05 - Goddard Welding cut off 4-1/2" & 8-5/8" csg. Cement fell 120

9/27/07 – Ellsworth Ready-Mix filled 4-1/2" and 8-5/8" with KCC District 2 slurry to surface as per KCC instructions (Greg Eaves). Ready Mix Ticket #37562.

9/28/05 - Kenney's Construction closed pit and covered casings.

KCC District #2 Slurry - 23 sxs/yard w/5.2 gal water/sk. Maximum 10% sand in slurry.

RECEIVED SEP 3 0 2005 KCC WICHITA