TO: STATE CORPORATION COMMISSION	API number: 15-163-21,972
CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING	<u>NESESE</u> /4 SEC. 13 , 07 S, 18 W 994 feet from S section line
WICHITA, KANSAS 67202	feet from E section line
Operator license# <u>30269</u>	Lease <u>City of Stockton</u> well #2-13
Operator: Argent Energy, Inc.	County Rooks
Address: 110 S. Main	Well total depth <u>3353</u> feet Conductor Pipe: 13 3/8 inch @ 78.5 feet
Wichita, Kansas 67202	Conductor Pipe: 13 3/8 inch @ 78.5 feet Surface pipe 8 5/8 Inch @ 1278 feet
Aband. oil well <u>X</u> , Gas well, Ing	out well, SWD, D & A
Plugging contractor: Plains Inc.	License#_4072_
Address: Ness City, Kansas 67560	
Company to plug at: Hour: P.M. Day:	4 Month: April Year: 94
Plugging proposal received from: Clint Base	
Company: Plains Inc.	Phone:
Were: Order 360 sxs. 65/35 pozmix - 10% gel - 500# hulls.	
Allied Cement Company. Alt. I complete to anhy.	
Critical area shot control 50	below base salt.
Plugging Proposal Received by: Carl Go	oodrow
Plugging operations attended by agent? All[X], Part[], None[]	
Completed: Hour: 1:45P.M., Day: 4 , Month: April , Year: 94	
Actual plugging report: 13 3/8" set a	t 78.5' w/100 sxs. cwc. 8 5/8" set
at 1278 w/450 sxs. cwc. 5 1/2" set at 3349 w/150 sxs. O.H. 3349 - 3353 Critical area shot control at 1750. Mix and pump down 5 1/2"	
W/235 sxs. cement blend with 500# hulls mixed in to Max. P.S.T. 900#	
125 SXS. Cement blend to Max. P.S.I. 9	100#. Close in P.S.I. 500#.
Plug complete.	E COME CYCLE
	wn 8 5/8" - 5 1/2" annulus with 00#. Close in P.S.I. 500#. STATE CONTOUR TON COMMISSION APPORTUNED A
Remarks:	Anhy plugaves & NO NO.
Bottom plug(in place):YES,CALC_>	NODakota plug:YESNO
Condition of casing(in hole):GOOD Bottom plug(in place):YES ,CALC > Plugged through TUBING ,CASING >	C. Elevation: GL GL
I did[N]VOidCof] observe the p	
DATE	$(agent) \qquad 4-7-94$
40311	Form CP-2/3