STATE CORPORATION COMMISSION OF KANSAS OIL & GAS CONSERVATION DIVISION	API NO. 15 - 163-22,537 -00-00				
WELL COMPLETION OR RECOMPLETION FORM ACO-1 WELL HISTORY	County Rooks				
DESCRIPTION OF WELL AND LEASE	NE NE SE Sec. 24 Twp. 7s Rge. 18 X West				
Operator: license # 8925 name Liberty Operations & Completions, Inc. address 308 West Mill	.2331 Ft North from Southeast Corner of Section Southeast Corner of Section (Note: locate well in section plat below)				
City/State/Zip Plainville, Ks 67663	Lease Name				
Operator Contact Person Charles G. Comeau Phone 913-434-4686	Field Name Riffe				
Contractor: license #	Producing Formation Arbuckle Elevation: Ground 1769! KB 1774!				
	Section Plat				
Wellsite Geologist Mark Torr Phone 913-628-3131 PURCHASER Koch Oil Designate Type of Completion	5280 4950 4620 4290 2360				
New Well Re-Entry Workover	3630				
□ Oil □ SWD □ Temp Abd □ Gas □ Inj □ Delayed Comp. □ Dry □ Other (Core, Water Supply etc.) STATE O	RECEIVED 2640 0RPORATION COMPTEE: 1980				
Operator	TU 1 1 20 990				
Well Name	hita, Kansas 82,4 4,4 4,5 6,6 6,6 6,7 5,7 5,7 5,7 5,7 5,7 5,7 5,7 5,7 5,7 5				
WELL HISTORY Drilling Method:	WATER SUPPLY INFORMATION				
.10-23-84	Source of Water: From City of Stockton Division of Water Resources Permit #				
3267. 3267. Total Depth PBTD	☐ Groundwater Ft North From Southeast Corner and (Well) Ft. West From Southeast Corner of Sec Twp Rge ☐ East ☐ West				
Amount of Surface Pipe Set and Cemented at 13.3/8 feet 8 5/8 feet	☐ Surface Water Ft North From Sourtheast Corner and (Stream, Pond etc.) Ft West From Southeast Corner				
Multiple Stage Cementing Collar Used? ☐ Yes ☒ No Longstring surface set	Sec Twp Rge East West				
If Yes, Show Depth Set feet	☐ Other (explain)(purchased from city, R.W.D.#)				
If alternate 2 completion, cement circulated from	Disposition of Produced Water: 🔯 Disposal				
	Docket # CD-38323 (C-21,881)				
INSTRUCTIONS: This form shall be completed in duplicate and filed Wichita, Kansas 67202, within 90 days after completion or recompletion of any	d with the Kansas Corporation Commission, 200 Colorado Derby Building, well. Rules 82-3-130 and 82-3-107 apply.				
Information on side two of this form will be held confidential for a period of 12 for confidentiality in excess of 12 months.	months if requested in writing and submitted with the form. See rule 82-3-107				
One copy of all wireline logs and drillers time log shall be attached with thi all temporarily abandoned wells.	s form. Submit CP-4 form with all plugged wells. Submit CP-111 form with				
All requirements of the statutes, rules, and regulations promulgated to regula herein are complete and correct to the best of my knowledge.					
Signature Masser	K.C.C. OFFICE USE ONLY F				
Charles G. Comeau	12-10-84. Distribution				
Subscribed and sworn to before me this . 10 day of OLCEMBED.	□ SWD/Rep □ NGPA				
	(Specify)				
NOTA	Form ACO-1 (7-84) ARY PUBLIC OF KANSAS 3-9-88				

SIDE TWO

Operator Name Liberty. Operations. &..... Lease Name ...MWM. M-6... Well# .1. SEC 24... TWP...7s.RGE....18... ☐ East Completions Inc.

WELL LOG

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all drill stem tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface during test. Attach extra sheet if more space is needed. Attach copy of log. NO LOGS WERE RUN

Drill Stem Tests Taken Samples Sent to Geologi Cores Taken	cal Survey	Yes Yes Yes	⊠ No ⊠ No ⊠ No	Formatio	n Description	
				: Name :	Тор	Bottom
LOG TOPS Anhydrite (top) Anhydrite (bottom) Topeka Heebner Toronto Lansing/KC Base/KC Arbuckle RTD	1191 1223 2705 2915 2941 2959 3182 3258 3267	(+583) (+551) (-931) (-1141) (-1167) (-1185) (-1408) (-1484) (-1493)		sand and shale shales shale and sand sand red bed shale anhydrite anhydrite shales shales lime and shale lime and shale	0' 90' 358' 685' 905' 960' 1191' 1205' 1223' 1262' 1733' 1910' 2189'	90' 358' 685' 905' 960' 1191' 1205' 1223' 1262' 1733' 1910' 2189'
	0201	(1450)		lime and shale	2447' 2687' 2828' 2952' 3049' 3160' 3267'	2687' 2828' 2952' 3049' 3160' 3267' R.T.D.

CASING RECORD N new used										
Purpose of string	Rep size hole drilled	oort all strings set - o size casing set (in O.D.)	conductor, surf weight lbs/ft.			# sacks	type and percent additives			
Conductor Stri Surface String " Production		.13.3/8" 8.5/8" 		89! 1204! 3261!	60-40pos 60-40pos common common	110 325 100 150	3%cc 2%gel 3%cc 2%gel			
PERFORATION RECORD shots per foot specify footage of each interval perforated				Acid, Fracture, Shot, Cement Squeeze Record (amount and kind of material used) Depth						
Open Hole 250 gallons, 15% INS with 5% checker sol. Retreated with 750 gallons, 15% INS, 5% checker sol.										
TUBING RECORD size 2 7/8 set at 3243.48 ' packer at Liner Run ☐ Yes ☒ No Date of First Production Producing method ☐ flowing ☒ pumping ☐ gas lift ☐ Other (explain)										
11–28–84 Estimated Production Per 24 Hours	35	Bbis	Gas	Water	Gas-	Oil Ratio	Gravity			
Disposition of gas:		\boxtimes	open hole	COMPLETION perforation		PRODU	CTION INTERVAL			

used on lease