4-<u>031852</u>

15-163-23093-00-00

TO:. STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API number: 15-163-23, 239 NW SE NW /4 SEC. 26 , 07 S, 17 W 3630 feet from S section line 3630 feet from E section line
Operator license# 5140	Lease Reed well # 1
Operator: Frontier Oil Company	Well total depth 3100 feet
Address: 125 N. Market #1720 Wichita, Kansas 67202	Well total depth <u>3100</u> feet Conductor Pipe: <u>13 3/8</u> inch @ <u>101</u> feet Surface pipe 8 5/8 Inch @ <u>1106</u> feet
Aband. oil well <u>X</u> , Gas well <u></u> , Inpo	ut well, SWD, D & A
Plugging contractor: <u>Kelso Casing Pulling</u> License# 6050	
Address: Chase, Kansas 67524	
Company to plug at: Hour: P.M. Day:	1 Month: September Year: 93
Plugging proposal received from: <u>Dave</u>	
Company: Kelso Casing Pulling Phone:	
Were: Order 275 sxs. 65/35 pozmix - 10% gel 500# hulls. Allied Cement Company. Sand and common cement.	
Plugging Proposal Received by: Carl Go	
Plugging operations attended by agent? All[X], Part[], None[]	
Completed: Hour: 1:45P.M., Day: 1 , Month: September , Year: 93 Actual plugging report: 13 3/8" set @ 101' w/75 sxs. cwc. 8 5/8" set @ 1106' w/400 sxs. cwc. 4 1/2" set @ 3010' w/120 sxs. P.B.T.D. 2740'. Perf. 2644' - 2654'. Sand back to 2590' with 4 sxs. common cement on sand with bailer. Shot free @ 2030'. Pull casing to 1550' circulated cement and hulls to surface. Laid down 4 1/2" casing topped off 8 5/8". Used total 275 sxs. cement blend with 500# hulls mixed. Plug complete.	
Remarks:Condition of casing(in hole):GOOD_X_BADAnhy.plug:YESX_NOBottom plug(in place):YESX_,CALC,NODakota plug:YES_X_,NORECEIVED plugged through TUBING, CASING_X Elevation:GLSTATE CORPORATION COMMISSION	
I dat 0 / Gia bot[] observe the p	3EF 2 2 1773
DATE 9-23-93	(agent) 927-93 Form CP-2/9NSERVATION DIVISION Wichita, Kansas