

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-163-21765-00-00  
Spot: CSESENE Sec/Twnshp/Rge: 19-7S-19W  
2970 feet from S Section Line, 330 feet from E Section Line  
Lease/Unit Name: SCHOELLER Well Number: 3  
County: ROOKS Total Vertical Depth: 3468 feet

Operator License No.: 32819  
Op Name: BAIRD OIL COMPANY LLC  
Address: 113 W. MAIN - PO BOX 428  
LOGAN, KS 67646

Conductor Pipe: Size feet:  
Surface Casing: Size 8.625 feet: 238 165 SX CMT  
Production: Size 5.5 feet: 3448 235 SX CMT \$ 112.71  
Liner: Size feet:

Well Type: OIL UIC Docket No: Date/Time to Plug: 05/22/2001 8:00 AM  
Plug Co. License No.: 32819 Plug Co. Name: BAIRD OIL COMPANY LLC  
Proposal Rcvd. from: JIM R. BAIRD Company: BAIRD OIL COMPANY LLC Phone: (785) 689-7456

Proposed Plugging Method: Order 300 sxs 60/40 pozmix - 10% gel - 200# hulls.

Plugging Proposal Received By: CARL GOODROW Witness Type: Plugging Operations 100% Witnessed (Complete)  
Date/Time Plugging Completed: 05/22/2001 9:30 AM KCC Agent: CARL GOODROW

Actual Plugging Report:

8 5/8" set at 238' w/165 sxs cwc. 5 1/2" set at 3448' w/235 sxs.  
Prod. Perfs 3324' - 3388'.  
Squeezed 5 1/2" w/240 sxs cement blend with 200# hulls to Max. P.S.I. 500#. Held.  
Squeezed 8 5/8" w/50 sxs cement blend to Max. P.S.I. 300#. Held.  
Plug complete.

INVOICED  
DATE 6-6-01  
INV. NO. 2001061897

RECEIVED  
KANSAS CORPORATION COMMISSION  
JUN 6 2001  
06-06-2001  
CONSERVATION DIVISION

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: CSG

District: 04

ND

Signed Carl Goodrow  
(TECHNICIAN)

MAY 30 2001

BAIRD OIL COMPANY  
BOX 7

REPLACEMENT CARD


19-7-19W  
SE SE NE

LOGAN, KS. 67646

#3 SCHOELLER

CONTR ABERCROMBIE DRILLING, INC. CTY ROOKS

GEOL \_\_\_\_\_ FIELD US-24



ELV 2011 KB SPD 8/14/82 CARD ISSUED 1/6/83 IP P 22.75 BO & 433

2006 GL

BWPD

API 15-163-21,765

ARB OH 3448-3468

LOG	Tops	Depth/Datum
ANH		1516 + 495
B/ANH		1549 + 462
TOP		2953 - 942
HEEB		3154 - 1143
TOR		3182 - 1171
LANS		3194 - 1183
SEV SH		3312 - 1301
BKC		3398 - 1387
ARB		3446 - 1435
LTD		3467 - 1456
RTD		3468 - 1457

8 5/8 " 238 / 165SX, 5 1/2 " 3448  
DST (1) 3310-42 (LKC) / 45-45-45-45, 310' GIP, REC 92' CL GSY OIL, 52' HOCM, SIP 841-1076#, FP 30-50 / 60-60#  
DST (2) 3336-60 (LKC) / 45-45-45-45, 20' GIP, REC 10' CL GSY OIL, 20' OCM, SIP 109-60#, FP 20-20 / 20-20#  
DST (3) 3355-77 (LKC) / 45-45-45-45, 226' GIP, REC 59' CL GSY OIL, 62' GSY OCM, SIP 1057-1047#, FP 40-40 / 60-60#  
DST (4) 3370-3400 (LKC) / 45-45-45-45, REC 20' CL GSY OIL, 62' GSY OCM, SIP 811-752#, FP 20-20 / 40-40#  
DST (5) 3444-68 (ARB) / 45-45-45-45, 488' GIP, REC 2074' CL GSY OIL, 61' HOCM, SIP 988-988#, FP 169-644#, FP 693-841#  
MICT - CO, (ARB OH), SWB DWN, GSO, NAT, POP, P 22.75 BO & 433 BWPD (GR 31° AT 60°), 6/24/83

INFO RELEASED: 10/17/85 - ADDED WELL INFO  
NOTE: INFO RELEASED: 10/25/84 - WAS TIGHT HOLE