

6 010516

FEB 27 1987

API NUMBER 15-065-22353-00-00

SW, SEC. 22, T. 7 S, R. 22 (W) W

3300 lde^o feet from S section line

2970 feet from E section line

Lease Name Worcester Well # 2

County Graham 123.70

Well Total Depth 3806 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 209

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 7076

Operator: Black Diamond oil

Name & Address 1105 E 30th

Hays KS.

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well (D&A)

Other well as hereinafter indicated _____

Plugging Contractor R. & C. Dolg. License Number _____

Address Hays KS.

Company to plug at: Hour: _____ Day: 27 Month: 2 Year: 19 87

Plugging proposal received from John Wise

(company name) R. & C. Dolg. (phone) _____

were: Order 215 3x cm. 60/40 permix 60% gel.

Heavy mud between all plugs.

Pump cm. down drill pipe

Elev 2197 Anhydrite 1855.88 Arbuckle Yes.

Dakota. 1500 Plugging Proposal Received by Dee F Balthazor

697-1000 (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ (Part) _____ None _____

Operations Completed: Hour: 11:45 AM Day: 27 Month: 2 Year: 19 87

ACTUAL PLUGGING REPORT 25 3x top Arbuckle

25 3x @ 1880

100 3x @ 1000

40 3x @ 250

10 3x @ 40

15 3x in Rat Hole

Remarks: _____
(If additional description is necessary, use BACK of this form)

INVOICED

DATE 3-6-87

INV. NO. 16284

Plug down 25' signed
Will fill w/ cement

Dee F Balthazor
(TECHNICIAN)

RECEIVED
STATE CORPORATION COMMISSION
3-6-87
MAR 8 1987

CONSERVATION DIVISION
Wichita, Kansas

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 2/22/87 month day year

API Number 15-065-22,353-00-00

OPERATOR: License # 7076 Name BLACK DIAMOND OIL, INC Address 1105 East 30th, Suite A City/State/Zip Hays, KS 67601 Contact Person Kenneth Vehige Phone 913.625.5891

C-E/2..SE..SW Sec.22.. Twp...7.. S, Rg...22.. West 3300 Ft. from South Line of Section 2970 Ft. from East Line of Section (Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 9087 Name R. & C. DRILLING CO., INC City/State Hays, KS 67601

Nearest lease or unit boundary line 330 feet County Graham

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary Gas Inj X Pool Ext Air Rotary OWWO Expl Wildcat Cable

Lease Name WORCESTER Well # 2 Ground surface elevation 2197 feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Depth to bottom of fresh water 150 Depth to bottom of usable water 1125 Surface pipe by Alternate 200 1 2 X Surface pipe planned to be set 3750 Conductor pipe required Arbuckle Projected Total Depth 3750 feet Formation

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 2/17/87 Signature of Operator or Agent Title Owner/Operator

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt. 2 This Authorization Expires 8-18-87 Approved By 2-18-87 Buck Finney - 200' S.P. - Hauling water 2/17/87 Spud - 2-20-87

C-E/2..SE..SW Sec.22.. Twp...7.. S, Rg...22.. West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Table with columns for plug depth, feet depth with, and sxs of. Includes handwritten note '(will call back)' and values for 1st through 5th plugs and rathole/mousehole.

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office after well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only: API #15-065-22,353 Surface casing of feet set with sxs at hours, 19 Alternate 1 or 2 surface pipe was used. Alternate 2 cementing was completed @ ft. depth with sxs on 19 Hole plugged, 19, agent

FEB 20 1987 STATE CONSERVATION COMMISSION MAR 3 1987 CONSERVATION DIVISION Wichita, Kansas