TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING

130 SOUTH MARKET, SUITE 2078 **WICHITA, KANSAS 67202** 

API Well Number: <u>15-051-21251-00-01</u>

2750

2130 feet from S Section Line,

Sec/Twnshp/Rge: 36-13S-20W Spot: NENWSE

1650 feet from E Section Line

Lease Name: ENGEL OWWO

Well #: 2

Total Vertical Depth: 3875 feet

Operator License No.: 101

Op Name: KCC FEE FUND PLUG

Address: 130 S. MARKET

**County: ELLIS** String Size

PROD 2.875

Depth (ft) Pulled (ft) Comment

w/unknown sxs cmt

SURF 8.625 256 w/150 sxs cmt

WICHITA, KS 67202

Well Type: SWD

**UIC Docket No:** 

**Date/Time to Plug:** 01/03/2006 3:00 PM

Plug Co. License No.: 3152 Proposal Revd. from: ED POE Plug Co. Name: POE SERVICING INC

Company: POE SERVICING INC

Phone: (785) 475-3422

Plugging

Method:

Proposed Ordered 75 sxs cement.

Well was drilled as Cedar Hills SWD but was never permitted.

Plugging Proposal Received By: HERB DEINES

WitnessType: COMPLETE (100%)

Date/Time Plugging Completed: 01/03/2006 3:45 PM

KCC Agent: ROGER MOSES

**Actual Plugging Report:** 

Perfs:

Perforated 2 7/8" tubing set at 1400' and circulated with cement upon completion. Tied to 2 7/8" tubing and squeezed with 52 sxs cement at constant 350# P.S.I. entire plugging. Total of 52 sxs 60/40 pozmix - 10% gel.

Remarks:

ALLIED CEMENTING COMPANY. POE WELL SERVICE-WATER.

Plugged through: TBG

District: 04

Signed Roger I W

(TECHNICIAN)

KECHWED

Form CP-2/3

JAN 19 2003

KCC WICHITA

JAN 06 2006

BOX 208	#2 ENGEL "OWWO" NE NW SE
RUSSELL, KS. 67665 CONTH RAPID WELL SERVICE, II	
GEOL	FIELD IRVIN
2216 KB CM 2/18/80 CARD 4/16/81 IF SWOW	
API 15-051-21,251-A	CED HILL 1200-50
ANH 1502 + 714 TOP 3221 -1005 HEEB 3472 -1256 25	D INFO: OPERATOR WAS KANSAS PETRO. NC. #1 ENGEL, SPD 11/29/76, 8 5/8" 56/150sx; completed as d&a/cong
cong 3866 -1650	2/7/76 st (1) 3687-3722/30-30-60-60, REC 155'TH M W/SPKS OIL, SIP 1280-
N.S.	1267#, FP NA 37-1-79-76
ws @	1267#, FP NA  Sy-d-11-29-76  W INFO: RE-ENTERED 2/18/81, Pl 12-7-76  H DWN TO 3850', SET 2-7/8" T 2-78-80  2750, DRILL COLLAR STUCK IN  LE @ 1050, DROPPED BALL TO BTM,
PF 120	14UU, CMT TO SURF, PF (CED HILL) 30-50, ac 500 g (28%). swb bk
WICHITA, KANSAS SET	, swow - injection rate 1500 bwpd, r 1" fiberglas @ 1100