STATE OF KANSAS
STATE CORPORATION COMMISSION
CONSERVATION DIVISION
800 BITTING BUILDING
WICHITA, KANSAS

WELL PLUGGING APPLICATION FORM

Lease Owner Herndon Drilling Company	Address 524 Mayo Building, Tulsa, Oklahoma
(Applicant) Lease (Farm Name) SMITH	Well Mo. 1
Well Locationsw SE NE	
County Rooks	Tield Name (if any)
Was well log filed with applications	Yes . If not, explain:
Date and hour plugging is desired to	
Plugging of the well will be done in	n accordance with the Rules and
Regulations of the State Corporation	Commission, or with the approval
of the following exceptions: Explai	in fully any exceptions desired.
(Use an additional sheet if necessar	·y'
Name of the person on the lease in	charge of well for owner
J. L. Chew Address B	ox 526, Lyons, Kansas
Name of Plugging Contractor West Supp	ly Company, Chase, Kansas
Address	
Invoice covering assessment for plug	
Herndon Drilling Company Address Tu	sa, Oklahoma NOV 8, 19 49
and paymant will be guaranteed by a	HERNDON DRILLING COMPANY
PLUGGING PLE SEC 8 T 8 R 170 Date	Applicant of Acting Agent Vice-President



STATE OF KANSAS STATE CORPORATION COMMISSION

CONSERVATION DIVISION 800 BITTING BUILDING WICHITA, KANSAS

September 20, 1949

IN REPLY PLEASE REFER TO THIS SUBJECT

Well No. Lease

Description SE NE 8-3-17

County Rooks File No. 115-14

Herndon Drilling Co. Lyons, Ks.

Gentlemen:

This letter is your authority to plug the above subject well, in accordance with the Rules and Regulations of the State Corporation Commission. When you are ready to plug this well, please contact our District Plugging Supervisor, Mr.

STATE CORPORATION COIMISSION CONSERVATION DIVISION

BY: Cone at a solution of the solution of the

cc: DISTRICT PLUGGING SUPERVISOR

WELL LOG ONC. SMITH #

Spudding date: 12-14-48

Date casing set: 1-1-49

Location:

Date rotary completed: 12-30-48

Section 8-88-17W., Rooks County, Kansas

Date cable completed:

FROM	TO FORMATION	REMARKS
30	30 Clay and shale 45 Rock & Clay	
45 98 500	98 Shale and rock 500 Shale	Ran 5 Jts. 98.59" of used 13" Cag. cemented W/125 Sks bulk loof C.C.,
597 965	597 Sand 965 Shale and shells 1225 Shale and red be	
1225 1243 1285	1243 Anhydrite 1285 Anhydrite	Han 9 Jts. Csg., ren 24 Jts. Csg. comented
1370 1465	1370 Shale and shells 1465 Red bed 2070 Shale and shells	Ren 4 Jts. 10 thd. used 992231 8_5/8"
2870 2490	2490 Shale and lime 3030 Lime and shale	7°4*1 1250.23
3030 3286 3312	3286 Lime 3312 Broken lime TOTAL BEPTH	
		Ren 104 Jts. 3312.631 of new 5-1/2" D.D. Ceg.
		Hole corrected from 3312'to 3310'

Subscribed and sworn to before me this day of January

I certify the above and foregoing to be a struct and exact copy of the original driller's log on the Smith #1

HERNDON DRILLING COMPANY