Form CP-3 Rev. 6-26-62

KANSAS STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

RECEIVED STATE CORPORATION COMMISSION

J. P. Roberts
Assitant Director
500 Insurance Building
212 North Market
Wichita 2, Kansas

15-163-01100-00-00

NOV 19 1963 //-/9- /963 CONSERVATION DIVISION Wichita, Kansas

Operator's Full Name	Clinton Oil Co
Complete Address:	6810 West 54 Highway Wichita, Kansas
Lease Name	Peaslee Well No. 1
County	Rooks Total Depth 3435
Abandoned Oil Well G	as Well Input Well D & Ax
Other well as hereafter in	dicated:
Plugging Contractor:	Jones-Gebert Drg Co & Sun Cementing Co
Address:	License No.
	Peaslee Well No. 1 SW SW NW Sec. 10 Twp. 8 Rge. (E) (W) 18 Rooks Total Depth 3435 il Well Gas Well Input Well SWD Well D&A x as hereafter indicated: ntractor: Jones-Gebert Drg Co & Sun Cementing Co License No. completed: Hour 2pm Day 16 Month 11 Year 63 ell was plugged as follows: 160' circulated with cement. 160' circulated with heavy mud, set plug at 550', displaced 25 sax cement drill pipe, heavy mud to 180', set plug and displaced 25 sax cement drill pipe, heavy mud to 35', set plug, hulls and filled to bottom with cement. 18 W OICED Signed: Well Flugging Supervisor
The Above well was plugged	as follows:
8 5/8" 160' circulated with cement.	
Address: License No. Operation Completed: Hour 2pm Day 16 Month 11 Year 63 The Above well was plugged as follows:	
through drill pipe,	heavy mud to 180', set plug and displaced 25 sax cemer
•	*
cellar with cement.	Peaslee Well No. 1 SW SW NW Sec. 10 Twp. 8 Rge. (E) (W) 18 Rooks Total Depth 3435 Oil Well Gas Well Input Well SWD Well D&A X as hereafter indicated: ontractor: Jones-Gebert Drg Co & Sun Cementing Co License No. Completed: Hour 2pm Day 16 Month 11 Year 63 well was plugged as follows: 160' circulated with cement. ated hole with heavy mud, set plug at 550', displaced 25 sax cement and drill pipe, heavy mud to 180', set plug and displaced 25 sax cement and drill pipe, heavy mud to 35', set plug, hulls and filled to bottom with cement. Ling by Sun Cementing Co. Signed: Well Flugging Supervisor
Cementing by Sun Cem	Above well was plugged as follows: 3 5/8" 160' circulated with cement. Circulated hole with heavy mud, set plug at 550', displaced 25 sax cement chrough drill pipe, heavy mud to 180', set plug and displaced 25 sax cement chrough drill pipe, heavy mud to 35', set plug, hulls and filled to bottom callar with cement. Cementing by Sun Cementing Co. Signed: Signed:
I hereby certify that the	above well was plugged as herein stated.
INVOIC	
•	, — itugging supervisor