E-18,445

TO:,	API number: <u>15- 6-26-78 OWWO</u>
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	NW CE CW // CEC OF OF C
200 COLORADO DERBY BUILDING	990 feet from S section line
WICHITA, KANSAS 67202	3630 feet from E section line
	reet from a section fine
Operator license# 5364	Lease_ <u>Huntington_OWWO</u> well #_2
Operator: Beren Corporation	County Graham 124.47
Address: P.O. Box 723	Well total depth 3830 feet
Hays, Kansas 67601	Conductor Pipe: 0 inch @ 0 feet Surface pipe 8 5/8 Inch @ 260 feet
Aband. oil well, Gas well, Inp	out well <u>X</u> , SWD, D & A
Plugging contractor: Co Tools	License#
Address:	
Company to plug at: Hour: 1:30P.M Day:	19 Month: April Year: 93
Plugging proposal received from: Bob G	rant
Company: Beren Corporation	Phone: 913-628-6101
Were: Order 300 sxs. 65/35 posmix - Well located outside area of Wellingto	10% gel. and hulls.
	n sait area.
Plugging Proposal Pagained by: Garl G	
Plugging Proposal Received by: <u>Carl G</u> Plugging operations attended by agent?	All Y 1 Dart 1 None 1
Completed: Hour: 3:15P.M., Day: 19, Mo	
Actual plugging report: 8 5/8" to 260	'. 5 1/2" to 3880'. Stage collar
at 2140' and cemented to surface with Tied onto production casing. Mixed and	600 SXS. Perfs. 3675' - 3822'.
hulls. Cementing pressure 400# - 500#	Max. 1300#. Standing S.T.P.
1300#. Tied onto annulus and pumped 3	0 SXS. cement. Hole in surface
pipe with cement up to surface through	crack in soil surface near welling
base.	VED
	APR 30
Remarks: Allied Cementing.	Q 3. 100x
Condition of casing(in hole):GOOD X B	AD Anhy.plug: YES X NOW SON S
Bottom plug(in place):YES X ,CALC	NO Dakota plug: VES X No. 3
Plugged through TUBING, CASING_X	
I did N V O dic E] observe the p	lugging.
DATE 5-3-93	(agent) A ₩ Form CP-2/3
INV. NO. 37443	. o. iii or 273
The state of the s	