

15-065-02963-00-01

4-050201

11-2

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- -

SW SE SE /4 SEC. 21, 07 S, 25 W
330 feet from S section line
990 feet from E section line

Operator license# 9594Lease Blazier well # 203Operator: Greer Oil CompanyCounty Graham

Address: P.O. Box 2444
Ponca City, OK 74602
(405) 763-6355

Well total depth 3889 feet ^{126.39}
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 238 feet

Aband. oil well , Gas well , Input well , SWD X, D & A Plugging contractor: Allied Cementing License# Address: Company to plug at: Hour: A.M. Day: 2 Month: November Year: 94Plugging proposal received from: Tom GreerCompany: Phone:

Were: Surface casing 8 5/8" set @ 238' w/225 sxs.
Production casing 5 1/2" set @ 3889' w/175 sxs.
D.V. at 2175' w/600 sxs. Perfs. 1740' - 1860'
C.I.B.P. at 2000'. Elevation: 2536'.

RECEIVED
KANSAS CORPORATION COMMISSION
NOV 10 1994
11-10-1994
CONSERVATION DIVISION
WICHITA, KS

Plugging Proposal Received by: Herb DeinesPlugging operations attended by agent? All[X], Part[], None[]Completed: Hour: 2:00P.M., Day: 2, Month: November, Year: 94

Actual plugging report: Tied onto 5 1/2" casing pumped 180 sxs. 60/40
pozmix - 10% gel and 500# hulls down casing. Max. P.S.I. 1000#.
Shut in P.S.I. 500#. Backside 500# P.S.I.

Remarks:

Condition of casing(in hole): GOOD X BAD Anhy. plug: YES X NO
Bottom plug(in place): YES , CALC X, NO Dakota plug: YES X, NO
Plugged through TUBING , CASING X. Elevation: 2536 GL

I did [X] / did not observe the plugging.Mawin MillerDATE 11-30-94

(agent)

Form CP-2/3

INV. NO. 41763

11-2 FEB 16 1995