1-19 15-163-00622-00-00

4-041560

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- - 5-1953

SW SW SW /4 SEC. 28, 08 S, 17 W
330 feet from S section line
4950 feet from E section line

Operator license# 5135

Lease Stamper 'C' well # 1

Operator: John O. Farmer

County Rooks

Address: P.O. Box 352
Russell, Kansas 67665

Well total depth 3427 feet 111.38
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 165 feet w/125 sxs.

Aband. oil well X, Gas well ___, Input well ___, SWD ___, D & A ___

Plugging contractor: Allied Cementing License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: 9:00A.M. Day: 19 Month: January Year: 94

Plugging proposal received from: Duane Eichman

Company: John O. Farmer Phone:

Were: 5 1/2" casing set @ 3417' w/100 sxs. cement. Perf. @ 3058' - 3376'. Perfs salt @ 2250' - Anhy. @ 1615' - Dakota @ 810'. Ordered 250 sxs. 60/40 pozmix - 10% gel with 1/4# F.C. plus 500# hulls plus 5 sxs. gel.

1-25-94

RECEIVED
STATE CORPORATION COMMISSION
JAN 25 1994
CONSERVATION DIVISION
Wichita, Kansas

Plugging Proposal Received by: Dennis L. Hamel
Plugging operations attended by agent? All[X], Part[ ], None[ ]

Completed: Hour: 3:15P.M, Day: 19, Month: January, Year: 94

Actual plugging report: R.I.H. with tubing to 3100'. Spot 50 sxs. cement with 200# hulls followed with 5 sxs. gel at 2800'. Pull up to 2200' - spot 75 sxs. cement with 250# hulls - pull to 1200' - spot 60 sxs. cement to circulate at surface. Pull tubing. Squeeze casing with 40 sxs. cement. Max. 300#. S.I.P. 200#. Hooked-up to 8 5/8" S.P. Squeeze with 25 sxs. cement plus 50# hulls. Max. 400#. S.I.P. 200#.

Remarks:
Condition of casing(in hole): GOOD ___ BAD X Anhy.plug: YES X NO ___
Bottom plug(in place): YES X, CALC ___, NO ___ Dakota plug: YES X, NO ___
Plugged through TUBING X, CASING ___. Elevation: ___ GL

I did[X]/did not[ ] observe the plugging. Dennis L. Hamel

(agent)

Form CP-2/3

INVOICED
DATE FEB 02 1994
INV. NO. 39848