

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-193-20,111-00-00

NW, Sec. 24, T 7 S, R 31 (W)  
\_\_\_\_\_ feet from N/S section line  
\_\_\_\_\_ feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5816

Lease Name EL McCormick Well # 4

Operator: Gulf Corporation  
Name & P.O. Box 12116  
Address Oklahoma City, OK. 73157

County Thomas

Well Total Depth 4335 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 471

Abandoned Oil Well X Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Halliburton License Number \_\_\_\_\_

Address Oberlin

Company to plug at: Hour: P.M. Day: 16 Month: 12 Year: 1982

VERBAL PLUGGING ORDERS GIVEN TO Dale Wood

(company name) Gulf (phone) \_\_\_\_\_

were: Stage cement with 5 1/2 casing after shot at 2500.

Bottom Bridge plug at 4160', Cement and sand to 2560.

5 sx cement to 2500.

50/50 poz 6% gel

Signed Carl Goodnow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 7 P.M. Day: 16 Month: 12 Year: 1982

ACTUAL PLUGGING REPORT Shot at 2500, 2300, 1900, 1600

Squeezed and staged 8 gel

100 sx cement, 9 sx gel, 70 sx cement.

Remarks: TO @ 2500 Anhy. 2600.

↑  
Top of Cement

I hereby certify that the above plugging instructions were given as herein stated and that I (did / did not) observe this plugging.

INVOICED  
DATE 2-8-83  
2359-W

RECEIVED  
STATE CORPORATION COMMISSION  
01-31-1983  
JAN 31 1983  
CONSERVATION DIVISION  
Wichita, Kansas

Signed Carl Goodnow  
(TECHNICIAN)