FORM CB-1 12/93

APR 2 4 2006

FOR KCC USE:

MAR 2 9 2006

11 12 4			FORM MUST BE TYPED
EFFECTIVE DATE: 4-12-06	<u>`</u>	HTA KCC WICHITA FO	ORM MUST BE SIGNED
DISTRICT #	CATHODIC PROTECTION SOR		KS MUST BE FILLED IN
SGA7. XYesNo Must	t be approved by the K.C.C. sixty (6	0) days prior to commencing well.	
		Spot (Location) 9/9/9	East
Expected Spud (Starting) Date	رم ما 2006 ما 04 ما 13 م	NE SW SE Sec 27 Tup 3	1 S. Rg . 10. X West
	month / day year	1190' feet from South	North line of Section
OPERATOR: License #336	31		West line of Section
		(Circle directions from nearest outs	
ConocoPhillips		IS SECTION X REGULAR IRREGU	• •
Name: 25760 W. 343rd Stre	eet	(Spot well on the Section Plat on	
city/state/zip: Paola KS.	66071	county: BARBER	
	***************************************	·	•••••••
Contact Person: Joe Garrison		Lease Name: MP 205	ıı #. #1
Phone: (913) 294-2166	5 Ext. 19	Facility Name: BORGER CHICAG	0
Phone:	• • • • • • • • • • • • • • • • • • • •	Ground Surface Elevation:	50 Est
•	*	Control of the Contro	200 /
	6427	Cathodic Borenote Total Depth	79. Tr
CONTRACTOR: License #:	• • • • • • • • • • • • • • • • • • • •	Depth to Bedrock	•••••••••••••• ft.
/ Dorling Dr	rilling) Rosencemente . Bearis	WATER INFORMATIO	
Name:	ming / reserves	Aquifer Penetration: None	
	/	Depth to bottom of fresh water: Depth to bottom of usable water: Water well within one-quarter mile:	
Type Drilling Equipment:	.X. Mud Rotary Cable	Depth to bottom of usable water:	
	Air Rotary Other		7.00
CONSTRUCTION FEATURES		Public water supply well within one m	•
Length of Cathodic Surface (Nor Planned to be set:	n-Metallic) Casing	Water Source for Drilling Operations	
Planned to be set:	60	well farm pond	stream .A. other
Length of Conductor pipe (if ar	197):NONEft.	Water Well Location:	
		•••••	
Size of the borehole (I.D.): Cathodic surface casing size: .	17.5" inches	DWR Permit #:	······································
Cathodic surface casing size: .	10" inches	Standard Dimension Ratio (SDR) is = .	26
Cathodic surface casing central	izers set at depths of: .20.;	(cathodic surface 00 csg.in inches /	MWT in inches = SDR)
40 . 60 . 80 . 100 . 1	120 ; ; ;;;		
• • • • • • •		Annular space between borehole and c	asing will be grouted
Cathodic surface casing will to	erminate at:	with: Concrete /	Bentonite Cement
.X Above surface Surface	Vault Below Surface Vault		Bentonite clay
atalasa sastas adambas sitti ba	words Vac (12) at Death 44	Anode vent pipe will be set at:	4 44
	used: Yes No at Depthft.	Anode vent pipe will be set at:	. A Tt. above surface
Anode installation depths are:	200', 185', 170', 155',		CAPPO CO
		Anode conductor (backfill) material T	YPE: CARBO 60
V ~ 1.70° i ···· i 120° i ···· i	; ; ; ; ; .	# Bank to Bank of Bank (1)	
★ * 140';; 100;; 15' CENTERS → HOLE BUT	10" SURFACE	K Depth to BASE of Backfill installation Depth to TOP of Backfill installation	n material
		WAS: 8 HOLE 5 /20 Caurf.	LEG: 120 MINI SUNFACE PEG.
* NOTE: MAX. Permitted Depth	A=200 : AFFIDAVIT	WAS: B HOLE 3	20/ 1/20 / 10/ 10/ 10/ 10/
The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101,			
The undersigned hereby affirms t	that the drilling, completion and eve	ntual plugging of this well will compl	y with K.S.A. 55-101,
et. seq. It is agreed that the following minimum requirements will be met:			
 Notify the appropriate district office prior to spudding of and again before plugging well; 			
2. A copy of the approved notice of intent to drill shall be posted on each drilling rig;			
The minimum amount of cathodic surface casing as specified below shall be set by grouting to the top.			
 An agreement between the operator and the district office on plugs and placement is necessary prior to plugging; The appropriate district office will be notified before well is either plugged or casing is grouted in: 			
	t office will be notified before well STRICT OFFICE PRIOR TO ANY CEMENTING		ted in;
O. IN ALL CASES, MOTTET DE	SIRICI OFFICE PRIOR TO ANY CEMENTING	•	
I hereby certify that the state	ments made herein are true and to th	e bast of my knowledge and belief.	
	¥ / /		ect Assistant
Date:03/27/06 Signat	ture of Operator or Agent:		
	FOR KCC USE:		Corrosion Control
	API # 15- 007-23006-00-	00	
•	Conductor pipe required NONE	Teet Teries	1
* *	Approved by:	quired 60 feet	Ŋ
•	Approved by:	JAM 2-1-00	17
	This authorization expires: /C	1-7-06	• -
	(This authorization void if drill		
	6 months of effective date.)	Started within	, .
	Spud date: Agent	::	3
			-
REMEMBER TO:			
- File Drill Pit Application (form CDP-1) with Intent to Install; - File Completion Form CB-2 within 30 days of spud date;			
- Noti	fy appropriate district office 48 ho	urs prior to workover or re-entry:	12
- Şubmi	t plugging report (CB-4) within 30	days after plugging is completed.	0
Mail to: KCC - Conservation Division, 130 S. Market - Room 2078, Wichita, Kansas 67202-1286.			
Mail to: KCC - Conservation Di	IVISION, 150 S. Harket - Koom 20/8, 1	richita, Kansas 6/202-1286.	