4-050158

| TO: | API number: 15-163-23,219 -00-00 |
|--|--|
| STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 | SW NW SW /4 SEC. 13 , 08 S, 17 W 1650 feet from S section line 4950 feet from E section line |
| Operator license#30730 | Lease Chesney B well # 1 |
| Operator: Horizontal Dev. & Prod. Inc. | County Rooks |
| Address: Town&Country Vill. Suite 277 Palo Alto, California 94301 (415)325-6980 | Well total depth 3450 feet Conductor Pipe: inch @ feet Surface pipe 8 5/8 inch @ 210 feet |
| Aband. oil well, Gas well, Inp | ut well, SWD, D & A _X |
| Plugging contractor: Emphasis Oil Opera | ations License# 8241 |
| Address: | |
| Company to plug at: Hour: PM Day: | 28 Month: January Year: 1993 |
| Plugging proposal received from: Rick Finnsey | |
| Company: Emphasis Oil Operations | phone: |
| Were: Spot plugs through drill pipe w/ | heavy mud between all plugs. |
| 1st plug @ 3402 feet with 25 sacks | Rat hole: 15 KSACKS CEIVED Mousehole: 10 sacks Felorian COMMISSION |
| 2nd plug @ 1275 feet " 25 " | Mousehole: 10 sacks Feb 16 |
| 3rd plug @ <u>775</u> feet " 100 " | Mousehole: 10 sacks Feb 16/1993 |
| 4th plug @ 260 feet " 40 " | CONSERVATION DIVISION WICHITA, KS |
| 5th plug @ <u>40</u> feet " 10 Plugging Proposal Received by: <u>Marvin</u> Plugging operations attended by agent? | with 8 5/8" wiper plug L. Miller |
| Completed: Hour:8:30 PM , Day: 28 , Mon | nth: January , Year: 1993 |
| Actual plugging report: <u>Hole reported</u> Order 225 sx 60/40 pozmix w/ 6% gel and | d plugged as above. d 1/4# celloflake or flowcel per sk |
| Remarks:Elevation: <u>1950</u> , Anhydrite: <u>1260</u> Bottom plug (in place): Yes<u>X</u> | - <u>1291</u> feet, Anhydrite plug: <u>1275</u> ,Calc,No Arbuckle: <u>3402</u> |
| Did penetrate Arbuckle, cemented by Allied Cementing Company | |
| I did of did not [X] observe the plugging. muling Miller | |
| 2-17-93 | Marvin L. Miller P.I.R.T.II |
| ATE 373 4 9 | (agent) Form CP-2/3 |