

Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION
WELL PLUGGING RECORD
K.A.R. 82-3-117

RECEIVED
JUN 30 2006
Form CP-4
December 2003
Type or Print on this Form
Form must be Signed
All blanks must be Filled
KCC WICHITA

Lease Operator: McCoy Petroleum Corporation
Address: 8080 E. CENTRAL SUITE 300 WICHITA, KS 67206
Phone: (316) 636-2737 Operator License #: 5003
Type of Well: D & A Docket #:
The plugging proposal was approved on: 6-23-2006 (Date)
by: ERIC MACLAREN (KCC District Agent's Name)
Is ACO-1 filed? Yes No If not, is well log attached? Yes No
Producing Formation(s): List All (If needed attach another sheet)
Depth to Top: Bottom: T.D.
Depth to Top: Bottom: T.D.
Depth to Top: Bottom: T.D.

API Number: 15-083-21,517-00-00
Lease Name: BENISH 'A'
Well Number: # 1-15
Spot Location (QQQQ): NE - NE - NW -
330 Feet from North / South Section Line
2310 Feet from East / West Section Line
Sec. 15 Twp. 24 S. R. 22 East West
County: HODGEMAN
Date Well Completed: 6-23-2006
Plugging Commenced: 6-23-2006
Plugging Completed: 6-23-2006

Show depth and thickness of all water, oil and gas formations.

Table with 7 columns: Formation, Content, From, To, Size, Put In, Pulled Out. Includes handwritten notes: 633' 643', 0, KCC 717106 PCT perc p2/3

Describe in detail the manner in which the well is plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same depth placed from (bottom), to (top) for each plug set.

ALLIED CEMENTING PLUGGED W/123 SX 60/40 POZMIX, WITH 6% GEL AS FOLLOWS: SET 50 SX @ 1440', 50 SX @ 750', 20 SX @ 60', 15 SX IN RATHOLE. PLUG DOWN @ 3:00 AM

Name of Plugging Contractor: STERLING DRILLING CO. License #: 5142
Address: P.O. BOX 1006 PRATT, KANSAS 67124

Name of Party Responsible for Plugging Fees: MCCOY PETROLEUM CORPORATION
State of KANSAS County, SEDGWICK, ss.

SCOTT HAMPEL, VICE PRESIDENT-PRODUCTION (Employee of Operator) or (Operator) on above-described well, being first duly sworn on oath, says: That I have knowledge of the facts statements, and matters herein contained, and the log of the above-described well is as filed, and the same are true and correct, so help me God.
(Signature) Scott Hampel
(Address) 8080 E. CENTRAL - SUITE 300 WICHITA, KS 67206

SUBSCRIBED and SWORN TO before me this 29th day of JUNE, 20 06

Meryle S. King My Commission Expires: 2-07-2010
Notary Public



Mail to: KCC - Conservation Division, 130 S. Market - Room 2078, Wichita, Kansas 67202

PCT

RECEIVED
JUN 30 2006
KCC WICHITA

Sterling Drilling Company, Rig #1

Box 1006, Pratt, Kansas 67124-1006
Office Phone (620) 672-9508, Fax 672-9509

SAMPLE LOG

Benish 'A' 1-15

LOCATION: NE NE NW
API: 15-083-21517-00-00

Section 15 T 24s R 22w
Hodgeman County, Kansas

OWNER: McCoy Petroleum Corporation
CONTRACTOR: Sterling Drilling Company, Rig #1

COMMENCED: 06/14/06
COMPLETED: 06/24/06

TOTAL DEPTH: DRILLER 4670 FEET
LOGGER 4671 FEET

Ground Elevation: 2286
KB Elevation: 2297

LOG

0 -	2 FEET	Top Soil
2 -	170 FEET	Surface Sands and Clay
170 -	1610 FEET	Clays, Sandstone and Shales
1610 -	2550 FEET	Shales and Salt
2550 -	4670 FEET	Limestone/Shales

CASING RECORDS

Spud at 12:15 pm on 06/14/06. Drilled 12-1/4" hole to 643'. Ran 15 joints of new 23# 8-5/8" casing, tally 632.52' set at 643' KB. Welded collars all joints. Strapped bottom 3 joints. Cemented with 350 sx Common; 3% CC; 2% Gel. Cement did circulate. Plug down at 4:15 am on 06/15/06. Allied Cementing ticket # 23713.

PLUGGING RECORD

Plugging orders received from Eric Maclaren at 10:00 am on 06/22/06. Plugged using 123 sx of; 60/40 Poz with 6% Gel as follows: Heavy mud in hole, Bottom plug 50 sx at 1440', 2nd plug 50 sx at 720' and top plug 20 sx at 60' cemented to surface. Plugged rathole with 15 sx. Plugging completed at 3:00 am 06/23/06 by Allied Cementing. Ticket # 24317. Sterling reported plugging to KCC on 06/23/06.

DEVIATION SURVEYS

1/2 degree(s) at 643 feet
1 degree(s) at 4671 feet