

WAS: Contractor 6427 Rosencrantz-Bewus  
IS: Contractor 32525 C.P. Drilling

Contractor RECEIVED  
CORRECTED APR 3 2006

CORRECTION

FOR KCC USE:

EFFECTIVE DATE: 6-18-06

DISTRICT # 3  
SGA? Yes No

State of Kansas  
CATHODIC PROTECTION BOREHOLE INTENT

Must be approved by the K.C.C. sixty (60) days prior to commencing well.

KCC WICHITA

FORM CB-1 12/93  
FORM MUST BE TYPED  
ALL BLANKS MUST BE FILLED IN

Expected Spud (Starting) Date 4 10 2006  
month day year

Spot (Location) 0/0/0  
NW - NW - NW Sec 28 Twp 28 S Rg 17 East  
240 feet from South North line of Section  
40 feet from East West line of Section  
(Circle directions from nearest outside corner boundaries)

OPERATOR: License # 5952  
BP America Production Company

IS SECTION X REGULAR IRREGULAR?  
(Spot well on the Section Plat on Reverse Side)  
County: Wilson

Name: \_\_\_\_\_  
Address: 700 E. Main Street  
City/State/Zip: Fremont, MO 64746

Lease Name: MP 125.41 Well #: #1

Contact Person: Ted Hoffman

Phone: (816) 899-5604

Facility Name: Drumright-Humboldt  
Ground Surface Elevation: 899' EST  
Cathodic Borehole Total Depth: 250' ft.  
Depth to Bedrock: \_\_\_\_\_ ft.

\* CONTRACTOR: License #: 6427 507 32525  
Name: (Darling Drilling) Rosencrantz-Bewus  
C.P. Drilling

WATER INFORMATION:  
Aquifer Penetration: None X Single Multiple  
Depth to bottom of fresh water: 80'  
Depth to bottom of usable water: 130'  
Water well within one-quarter mile: yes X no  
Public water supply well within one mile: yes X no  
Water Source for Drilling Operations:  
well farm pond stream X other

Type Drilling Equipment: X Mud Rotary Cable  
Air Rotary Other

CONSTRUCTION FEATURES

Length of Cathodic Surface (Non-Metallic) Casing  
Planned to be set: 20' ft.  
Length of Conductor pipe (if any): none ft.

Size of the borehole (I.D.): 250' - 17.5" inches  
Cathodic surface casing size: 10" inches  
Cathodic surface casing centralizers set at depths of: 20';

DWR Permit #: \_\_\_\_\_  
Standard Dimension Ratio (SDR) is = 17.25  
(cathodic surface OD casg. in inches / MJT in inches = SDR)

Cathodic surface casing will terminate at:  
Above surface Surface Vault X Below Surface Vault

Annular space between borehole and casing will be grouted  
with: X Concrete Bentonite Cement  
Heat cement Bentonite clay

Pitless casing adaptor will be used: Yes No at Depth \_\_\_\_\_ ft.

Anode vent pipe will be set at: \_\_\_\_\_ ft. above surface

Anode installation depths are: 240; 230; 220; 210';  
200'; 190'; 180'; 170'; 160'; 150';

Anode conductor (backfill) material TYPE: Loresco SWS  
Depth to BASE of Backfill installation material: 130'  
Depth to TOP of Backfill installation material: 20'

\* Max Permitted Depth = 250'

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq. It is agreed that the following minimum requirements will be met:

1. Notify the appropriate district office prior to spudding of and again before plugging well;
2. A copy of the approved notice of intent to drill shall be posted on each drilling rig;
3. The minimum amount of cathodic surface casing as specified below shall be set by grouting to the top.
4. An agreement between the operator and the district office on plugs and placement is necessary prior to plugging;
5. The appropriate district office will be notified before well is either plugged or casing is grouted in;
6. IN ALL CASES, NOTIFY DISTRICT OFFICE PRIOR TO ANY CEMENTING.

I hereby certify that the statements made herein are true and to the best of my knowledge and belief.

Date: March 30, 2006 Signature of Operator or Agent: Dehly Anders Title: Administrative Assistant  
Mesa Corrosion Control

RECEIVED  
AUG 10 2006  
KCC WICHITA

FOR KCC USE:  
API # 15- 205-26753-0000 ALT 3  
Conductor pipe required NONE feet  
Minimum cathodic surface casing required 20' feet  
Approved by: DPW 6-13-06 1044 8-11-06  
This authorization expires: 11-13-06  
(This authorization void if drilling not started within 6 months of effective date.)  
Spud date: \_\_\_\_\_ Agent: \_\_\_\_\_

REMEMBER TO:

- File Drill Pit Application (form CDP-1) with Intent to Install;
- File Completion Form CB-2 within 30 days of spud date;
- Notify appropriate district office 48 hours prior to workover or re-entry;
- Submit plugging report (CB-4) within 30 days after plugging is completed.

28  
28  
17E