API Number: 15-163-20,488 9-18 TO: STATE CORPORATION COMMISSION NE NW NE /4 SEC. 19 , 08 S, 16 W CONSERVATION DIVISION - PLUGGING 4950 feet from S section line 130 SOUTH MARKET, SUITE 2078 WICHITA, KANSAS 67202 1650 feet from E section line Operator license# 0000 Lease: Chesney Well # 1 County: Rooks Operator: State of Kansas Fee Fund Address: 2301 E. 13th Street Well total depth 3290 feet Conductor Pipe: 0 inch @ 0 sxs. Hays, Kansas 67601 Control #990012-001 Surface pipe 8 5/8 Inch @ 210 feet W/ 75 sxs. ABAND. oil well\_X, Gas well\_\_\_\_, Input well\_\_\_, SWD.\_\_\_\_, D&A\_\_\_\_ Plugging contractor: Kansas Corporation Commission License# -Address: 2301 E. 13th - Hays, Kansas 67601 Company to plug at: Hour: A.M. Day: 15 Month: September Year: 1998 Plugging proposal received from: Herb Deines Company: Kansas Corporation Commission Phone: 785-625-0550 Were: Ordered 320 sxs 60/40 pozmix - 10% gel with 600# hulls. 0 [-,] Plugging Proposal Received by: Herb Deines Plugging operations attended by agent? All[ ], Part[ X ], None[ ] Completed: Hour: 3:00 P.M. Day: 18 , Month: September , Year: 1998 Actual plugging report: Perforated salt section at 1650'. Anhy at 1200'. Dakota at 700'. Fluid level 400'. PBTD 3065'. Ran tubing to 1620'. Allied pumped 75 sxs 60/40 pozmix - 10% gel with 300# hulls. Pulled tubing to 695' and pumped 40 sxs with 150# hulls. Cement circulated. PTOH and squeezed 175 sxs with 100# hulls. Max. P.S.I. 300#. S.I.P. 200#. Hooked up to 8 5/8" and pumped 30 sxs cement with 50# hulls. Max. P.S.I. 300#. S.I.P. 200#. Remarks: Condition of casing(in hole): GOOD\_\_\_\_\_\_BAD\_\_\_\_ Anhy.plug: YES X NO\_\_\_\_ Bottom plug(in place): YES\_X , CALC\_\_\_\_, NO\_\_\_\_ Dakota plug: YES X , NO \_\_\_\_

Elevation: 1848

Kike Valle

(agent)

Form CP-2/3

Plugged through TUBING X , CASING ...

I did[ X ] / did not[ ] observe the plugging.