

4-070140

3-24

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Number: 15-163-23,304-0000

NW NW SW /4 SEC. 07, 08 S, 16 W
2310 feet from S section line
4950 feet from E section line

Operator license# 30730

Lease: Chesney Well # H-1

Operator: Horizontal Development
And Production

County: Rooks 108.55

Address: 23077 Pedernales Canyon
Spicewood, Texas 78669

Well total depth 3340 feet
Conductor Pipe: 0 inch @ 0 sxs.
Surface pipe 8 5/8 Inch @ 201 feet

ABAND. oil well X, Gas well, Input well, SWD., D&A

Plugging contractor: Quality Well Service License# 31925

Address: 249 E. Beth Dr. - Sterling, Kansas 67579

Company to plug at: Hour: 10:30 A.M. Day: 24 Month: March Year: 1999

Plugging proposal received from: Richard McIntyre

Company: Quality Well Service Phone: 316-278-2476

Were: 5 1/2" casing set at 3333'.
Perfs: 2964' - 3265'.
Middle Anhy 1245'. Base Dakota 786'.
Sand back perfs to 2896' w/5 sxs cement on top.
Ordered out 190 sxs 60/40 pozmix - 10% gel - 500# hulls.

Plugging Proposal Received by: Rich Williams

Plugging operations attended by agent? All [X], Part [], None []

Completed: Hour: 1:00 P.M. Day: 24, Month: March, Year: 1999

Actual plugging report: Sand perfs back to 2896' w/5 sxs cement on top. Quality shot 5 1/2" casing off at 2240'. Pulled to 1240'. Allied cement with 85 sxs 60/40 pozmix - 10% gel with 200# hulls. Pulled casing to 785'. Pumped 40 sxs cement with 200# hulls. Pulled casing to 250'. Pumped 55 sxs cement with 100# hulls. Circulated. Pulled all casing out. Hole stayed full.

RECEIVED
STATE CORPORATION COMMISSION

MAR 30 1999

3-30-99

Remarks:

Condition of casing(in hole): GOOD X BAD Anhy.plug: YES, Kansas NO
Bottom plug(in place): YES X, CALC, NO Dakota plug: YES X, NO
Plugged through TUBING, CASING X Elevation: 1936 GL

I did [X] / did not [] observe the plugging.

Richard Williams
(agent)

Form CP-2/3

INVOICED

DATE 4-2-99

INV. NO. 60767