

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Well Number: 15-163-21941-00-00  
Spot: SESWSW Sec/Twnshp/Rge: 12-10S-18W  
330 feet from S Section Line, 4290 feet from E Section Line  
Lease Name: BARDOT Well #: 3  
County: ROOKS Total Vertical Depth: 3873 feet

Operator License No.: 32278  
Op Name: TENGASCO, INC.  
Address: 1327 NOOSE ROAD PO BOX 458  
HAYS, KS 67601

String	Size	Depth (ft)	Pulled (ft)	Comment
CIBP		3450		
DVT		1523		550 SX CMT
PROD	4.5	3858	0	275 SX
SURF	8.625	278	0	170 SX

\$ 125.87

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 07/26/2006 8:00 AM  
Plug Co. License No.: 99998 Plug Co. Name: COMPANY TOOLS  
Proposal Rcvd. from: GARY WAGNER Company: TENGASCO, INC. Phone: (785) 625-6374

Proposed Plugging Method: Ordered out 225 sxs 60/40 pozmix - 10% gel - 500# hulls.  
DV Tool at 1527' w/550 sxs. CIBP at 3450'.

Plugging Proposal Received By: RICHARD WILLIAMS Witness Type: COMPLETE (100%)  
Date/Time Plugging Completed: 07/26/2006 10:00 AM KCC Agent: RICHARD WILLIAMS

Actual Plugging Report:

07-25-2006 - Fisher Well Service sandline drilled CIBP at 3450' to 3620'.  
07-26-2006 - Allied pumped 200 sxs 60/40 pozmix - 10% gel with 500# hulls.  
Max. P.S.I. 750#. S.I.P. 350#.  
Backside instant pressure 500#.

Perfs:

Top	Bot	Thru	Comments
3603	3617		
3566	3581		
3564	3567		
3556	3560		
3546	3550		
3518	3524		

INVOICED

DATE 8-3-06  
2007060308

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: CSG

District: 04

HO

Signed Richard Williams  
(TECHNICIAN)

RECEIVED

AUG 8 2 2006

KCC WICHITA

Form CP-2/3

JUL 28 2006

RET

FRONTIER OIL COMPANY

1720 KSB&T BUILDING

WICHITA, KS 67202

#3 BARDOT


12-10-18W  
SE SW SW

CONTR RED TIGER DRILLING CO.

CTY ROOKS

GEOLOGICAL STEVEN ANGLE

FIELD PLAINVILLE



ELV 2164 KB SPD 1/21/83

CARD ISSUED 3/31/83

IP OIL WELL

API 15-163-21,941

LKC 3518-3617 OA

SMP	Tops	Depth-Datum	
			8 5/8 " 278/170SX, 4 1/2 " 3858/275SX
ANH	1501 + 663		DST (1) 3343-3460 (SHAW, LKC) / 60-30-60-30, REC 129' MSW, SIP 1045-1035#, FP 83-104 / 104-124#
BRNVLE	2819- 655		DST (2) 3460-3536 (LKC) / 60-30-60-30, REC 578' SOCM, SIP 1158-1117#, FP 83-207 / 228-311#
TARK	2922- 758		DST (3) 3536-56 (LKC) / 15-30-15-30, REC 2' M, NS, SIP 83-73#, FP 42-42 / 42-42#
TOP	3125- 961		DST (4) 3556-3660 (LKC) / 30-30-15-30, REC 20' M, NS, SIP 456-456#, FP 104-104 / 124-124#
HEEB	3348-1184		DST (5) 3648-96 (PENN) / 60-30-60-30, REC 10' M, NS, NO PRESSURES - RECORDER FAILED
TOR	3365-1201		MICT - CO, DROVE DV TOOL TO BTM, PF (LKC) 1 / 3581, 1 / 3603, 1 / 3617, ONFU 30' FL, SWB DWN & REC 1:2 BOM, AC 1500G (15% REG), SWB 3 48 BF (55% OIL) / 1 HR, 2 32 BF (70% OIL) / 2ND HR, 2.32 BF (80% OIL) / 3RD HR, 1.16 BF (90% OIL) / 4TH HR, 1.16 BF (90% OIL) / 5TH HR, PF (LKC) 1 / 3566, 1 / 3558, 1 / 3548, SET 4 1/2 " PLUG AT 3775, SWB DWN, AC 1500G (15% REG), SWB DWN, SET 4 1/2 " PLUG AT 3530, PF (LKC) 3518-24, W / 4 SPF, ONFU 220' OIL, SWB 3.48 BO, AC 500G (15% REG), SWB DWN, RE-AC 1000G (15% REG), SWB 4.06 BF (75% OIL) / 1 HR, 4.64 BF (95% OIL) / 2ND HR, 4.64 BF (95% OIL) / 3RD HR, 3.48 BF (95% OIL) / 4TH HR, 3.48 BF (95% OIL) / 5TH HR, ONFU 1500' FL, DROVE PLUGS TO BTM, SET 2 3/8 " TBG AT 3687, POP, 2/21/83
LKC	3389-1225		
BKC	3650-1486		
SIMP DOL	3719-1555		
ARB	3742-1578		
RTD	3873-1709		