TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-065-01909-00-01
Spot: NENE **Sec/Twnshp/Rge:** 11-10S-25W
4620 feet from S Section Line, 660 feet from E Section Line
Lease Name: EAST ELRICK **Well #:** 2-3
County: GRAHAM **Total Vertical Depth:** 3998 feet

Operator License No.: 5010
Op Name: KNIGHTON OIL COMPANY, INC.
Address: 221 S. BROADWAY, STE. 710
WICHITA, KS 67202

String	Size	Depth (ft)	Pulled (ft)	Comment
PROD	4.5	3997	0	125 SX CMT
SURF	8.625	328	0	325 SX CMT

#129.94

Well Type: EOR **UIC Docket No:** E15410.4 **Date/Time to Plug:** 09/13/2006 9:00 AM
Plug Co. License No.: 4072 **Plug Co. Name:** PLAINS, INC
Proposal Rcvd. from: KEN WERNER **Company:** KNIGHTON OIL COMPANY, INC. **Phone:** (785) 623-4081

Proposed Plugging Method: Ordered 250 sxs cement and 800# hulls.

Plugging Proposal Received By: HERB DEINES **WitnessType:** COMPLETE (100%)
Date/Time Plugging Completed: 09/13/2006 3:00 PM **KCC Agent:** ROGER MOSES

Actual Plugging Report:

DV Tool at 2151' w/135 bbls Kempac.
Squeezed at 3360' - 3389' w/100 sxs cement.
Ran tubing to 3851' - mixed 75 sxs cement with 250# hulls.
Pulled tubing to 1861' - circulated with 75 sxs cement with 300# hulls.
Pulled all tubing - squeezed 4 1/2" casing with 50 sxs cement and 250# hulls.
Max. P.S.I. 750#. S.I.P. 500#.
Tied to 8 5/8" x 4 1/2" - squeezed 10 sxs cement.
Max. P.S.I. 500#. S.I.P. 500#.
Total of 210 sxs 60/40 pozmix - 10% gel and 800# hulls.

Perfs:

Top	Bot	Thru	Comments
3828	3970		

RECEIVED
SEP 21 2006
KCC WICHITA

INVOICED
DATE 9/22/06
INV. NO. 2007060574

Remarks: LEASE ORIGINALLY KNOWN AS BILLINGER #3. ALLIED CEMENTING COMPANY. PFEIFER TANK-WATER.

Plugged through: TBG

District: 04

Signed Roger L. Moses
(TECHNICIAN)

Form CP-2/3

SEP 18 2006

15-065-01909-CO-01

TEXACO, INC #3 BILLINGER 11-10-25W C NE NE

Contr. K & E DRLG GRAHAM County

E2507 RB Comm. Comp. 10-13-61 IP 72 BOPD/LANS

Tops	Depth	Datum
Anh		+377
HEEB	3752	-1245
TOR	3773	-1266
LANS	3787	-1280
TD	3998	-1491

INDEPENDENT OIL & GAS SERVICE
WICHITA, KANSAS

Casing
8" 328
4" 3997

CO 3988: PERF LANS 'J' ZN 13/3966-70: SH OIL: ACID 1000: SWB 11 BO, NW/5 HRS REACID 2000: SWB 77 BO & 48 BW: REPERF 3966-77½: 95 BO, NW/7 HRS: BP 3958: 15/3948-53: SWB 38.26 BO, NW/3 HRS: PULL BP: TST 36.36 BO, NW: BP 3850: 12/3828-32: SWB DRY & TST DRY: PKR 3802: SQZ PERFS 3828-32: PULLED BP: CO 3988: 600' FIH

ELRICK POOL

