4-<u>090557</u> /-26

To:	API number: 15-141-20,330 -00-00
STATE CORPORATION COMMISSION	70'E.of
CONSERVATION DIVISION - PLUGGING	SW SE NE /4 SEC. 06 , 10 S, 12 W
130 SOUTH MARKET, SUITE 2078	2970 feet from S section line
WICHITA, KANSAS 67202	feet from E section line
Operator license#_5184	Lease:Kendig "E" Well #1
Onesetes. Chieffe Oil Duedware Tre	County: Osborne 100.91
Operator: Shields Oil Producers, Inc.	County: Osborne /DUIT
Address: Shields Building	Well total depth 3107 feet
Russell, Kansas 67665	Conductor Pipe: 0 inch 0 0 feet Surface pipe 8% Inch 0 221 feet
Aband. oil well, Gas well, Input w	well, SWD, D & A_X
Plugging contractor: Shields Drilling Comp	pany License# 5184
Address: Russell, Kansas 67665	
Company to plug at: Hour: - Day: 24	
Plugging proposal received from: Burton I	Beery
Company: Shields Drilling Company	Phone:
Were: Order 175 sxs 60/40 posmix - 6% gel.	a
Spot all plugs through drill pipe with heavy	
	s
Plugging Proposal Received by: Ed Schumach	
Plugging operations attended by agent? All	[], Part[], None[X]
Completed: Hour: 10:30 P.M. Day: 26	, Month: January , Year: 1997
	Month. January , Year: 1997
Actual plugging report:	
1st. Plug at 920' w/20 sxs cement.	
2nd. Plug at 590' w/80 sxs cement.	
3rd. Plug at 270' w/40 sxs cement.	
4th. Plug at 40' w/10 sxs cement.	· · · · · · · · · · · · · · · · · · ·
15 sxs in rathole.	
10 sxs in mousehole	
Arbuckle - no - Anhydrite 906'.	
Remarks:Allied Cementing	
Condition of casing(in hole): GOOD	BAD Anhy.plug: YES X NO
Bottom plug(in place): YES, CALC	_, NO Dakota plug: YESX_, NO
Plugged through TUBING, CASING	Elevation: 1789 GL
I Nav () / Git not [x] observe the pluggi	ing. Ed Achumacher
FEB 1 0 1907	(agent)
ATE	Form CP-2/3
4155	
LEGATE ARTES AND AND ADDRESS OF THE PERSON NAMED AND ADDRESS O	