## 4-<u>070131</u>

10000	
TO:	API Number: <u>15-141-20,344-0000</u>
STATE CORPORATION COMMISSION	100'W.of
CONSERVATION DIVISION - PLUGGING	<u>NE NE SE  /4 SEC. 06, 10 S, 12 W</u>
130 SOUTH MARKET, SUITE 2078	
	feet from S section line
WICHITA, KANSAS 67202	feet from E section line
Operator license#_3345	Lease: Steinle-Yarnell Well # 3 Twin
Operator: LeRoy E. Tobias	County: Osborne 100.75
operator. Heroy H. Tobras	country. Osborne
Address: 19180 Mellard Road	Well total depth 3100 feet
Bunker Hill, Kansas 67626	Conductor Pipe: 0 inch @ 0 sxs.
	Surface pipe 8 5/8 Inch @ 207 feet
Address of the second s	W/150 sxs.
ABAND. oil well, Gas well, Input well	
Plugging contractor: VonFeldt Drilling, I	nc. License# 9431
Address: 719 W. Witt Avenue - P.O. Box 61	1 - Russell, Kansas 67665-0611
Company to plug at: Hour: P.M. Day. 2	2 Month: October Year: 1998
Plugging proposal received from: Bill Owe	<u>n</u>
Company: VonFeldt Drilling, Inc. Phone: 785-483-6446	
Were: Ordered 200 sxs 60/40 pozmix - 6% ge	l - 1/4# floseal per sack - one 8 5/8" W.P.
Spot plug through drill pipe with he	avy drilling mud between all plugs.
Plugging Proposal Received by: Rich Wil	
Plugging operations attended by agent? All[	], Part[ ], None[ X ]
Completed: Hour: 1:45 A.M. Day: 22 , Mon	th. October 77
completed. Hour. 1.45 A.M. Day: 22 , Moli	th: October Year 1998
Actual plugging report: No arbuckle cut.	STATE CORPORATION COMMISSION
1st Plug at 915' w/25 sxs Anhy. 898' - 93	
	4 / 11,00,103
2nd Plug at 630' w/100 sxs Dakota 330'.	
3rd Plug at 257' w/40 sxs Surface pipe +	50'. /~//~97
4th Plug at $40$ ' w/10 sxs. One 8 5/8" Wiper	Plug. CONSERVATION DIVISION
Rathole with 15 sxs Mousehole with 10 sx	s. Wichita, Kansas
Remarks:	
The state of the s	7.0
Condition of casing (in hole): GOODBi	
Bottom plug(in place): YES, CALC, No	O Dakota plug: YESX_, NO
Plugged through TUBING, CASING	Elevation: 1780 GL
- 1175 - 7 / -15	$\frac{1}{1}$
I $\operatorname{did}[]$ / $\operatorname{did}$ not[ $old x$ ] observe the pluggin	
	(agent) Form CP-2/3
	FUIII CF"2/3

Ø

1-12-99