

STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - Plugging Section  
130 S. Market, Room 2078  
Wichita, Kansas 67202

4-24  
15-035-19436-00-00  
API NUMBER: 7-18-59

SE SE NW, SECTION 11 TOWNSHIP 30 RANGE 06E

OPERATOR LICENSE # 5437 2970 FEET FROM S SECTION LINE  
OPERATOR TOMCO OIL, INC. 2970 FEET FROM E SECTION LINE  
NAME & P.O. BOX 280  
ADDRESS DOUGLAS, KS 67039 LEASE NAME: BLAIR #8  
COUNTY: COWLEY  
WELL TOTAL DEPTH: 1837' 59.71  
PIPE:  
SURFACE CASING: 8 5/8 @ 201'

ABANDONED OIL WELL ☒ GAS WELL ☐ INPUT WELL ☐ SWD ☐ D&A ☐

OTHER WELL AS HEREINAFTER INDICATED: \_\_\_\_\_

PLUGGING CONTRACTOR: LONG DRILLING CO.  
ADDRESS: P.O. BOX 131 HAMILTON, KS 66853 LICENSE: 6112

COMPANY TO PLUG AT: HOUR: 12:30P.M. DAY: 24 MONTH: 04 YR: 1998

PLUGGING PROPOSAL RECEIVED FROM: TOM BLAIR  
COMPANY NAME: TOMCO OIL, INC. PHONE: (316) 747-2390  
WERE: BOTTOM PLUG: SAND BACK 50' ABOVE PERFORATIONS WITH 5 SX CEMENT ON TOP OF  
SAND. TOP PLUG: BUILD BRIDGE AT 270'. CEMENT FROM 270' TO SURFACE W/ 5 YDS  
OF SLURRY MIX.

RECEIVED  
KANSAS CORPORATION COMMISSION

PLUGGING PROPOSAL RECEIVED BY: DONALD HOBERCHT MAY 08 1998

PLUGGING OPERATIONS ATTENDED BY AGENT? ALL ☐ PART ☒ NONE ☐

CONSERVATION DIVISION  
WICHITA, KS

COMPLETED: HOUR: 2:00P.M. DAY: 24 MONTH: 04 YEAR: 1998

ACTUAL PLUGGING REPORT: SAND BACK TO 1590' DUMP 5 SX CEMENT ON TOP OF SAND. SHOT  
CASING AT 550', PULLED TO SURFACE. BUILT BRIDGE AT 270'. DUMPED SLURRY MIX  
FROM 270' TO SURFACE.

REMARKS: LEWIS & WEST CONCRETE, EL DORADO, KS #156

I DID OBSERVE THIS PLUGGING.

  
DONALD HOBERCHT

FORM CP-2/3  
REV. 3/90

INVOICED  
DATE MAY 11 1998  
INV. NO. 50518

pet