Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

WELL PLUGGING RECORD K.A.R. 82-3-117

Form CP-4
December 2003
Type or Print on this Form
Form must be Signed
All blanks must be Filled

0/31 E Cor		C.			API Number: 15	
Address: 3431 L CEI	ntral, Suite 100, Wi	chita, KS 6720	06		Lease Name: Fox	
Phone: (316)684	-8481 _{Oper}	ator License #: _	5056		Well Number: 1-34	1
011/6	as Percez/2	3 <i>PH</i>			Spot Location (QQ(QQ): 10'S&30'N - SE - SE -
Type of Well: Oll / Od (Oil, Gas D&A, SWD, ENH	<u> </u>	Doc	ket #: (If SW	'D or ENHR)	320 375 Feet from	
The plugging proposal w				(Date)	360 42 Z Feet from	East / West Section
by: Steve Durrant						
-					Sec. 34 Twp. 2	
Is ACO-1 filed? Ye	-	is well log attache	ed? ✓ Yes	∐No	County: Pawnee	04/38 01/1981 Per e
Producing Formation(s):	•				Date Well Complete	
	Depth to Top:				Plugging Commend	ed: 11-13-06
	Depth to Top:				Plugging Completed: 11-14-06	
	Depth to Top:	Bottor	n:	T.D		
Show depth and thickne		gas formations.				
Oil, Gas or Water Records Formation Content		From To Size			Surface Conductor & Production) Put In Pulled Out	
Formation	Content	rioiii	10		248	Fulled Out
		· · · · · · · · · · · · · · · · · · ·	 	8 5/8		
				4 1/2	4401	2230
	l.					
						d or methods used in introducing it
hole. If cement or other	r plugs were used, state	the character of	same depth p	laced from (bott	om), to (top) for each	
hole. If cement or other Sand at 4250', bail	r plugs were used, state led 4 sacks cement	the character of with bailer, p	same depth pulled slips,	placed from (bott had 18" streto	om), to (top) for each ch, ripped casing	plug set.
hole. If cement or other Sand at 4250', bail ripped casing at 2	r plugs were used, state led 4 sacks cement 230', worked pipe	the character of with bailer, p free, pulled o	same depth pulled slips, casing up to	placed from (bott had 18" streto o 1150', pum	om), to (top) for each ch, ripped casing aped 15 gel, 50 sa	plug set. at 2420', worked pipe,
hole. If cement or other Sand at 4250', bail ripped casing at 2	r plugs were used, state led 4 sacks cement 230', worked pipe	the character of with bailer, p free, pulled o	same depth pulled slips, casing up to	placed from (bott had 18" streto o 1150', pum	om), to (top) for each ch, ripped casing aped 15 gel, 50 sa	plug set. at 2420', worked pipe, acks cement, pulled up to 6
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks,	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun	the character of with bailer, p free, pulled on ped 40 sacks	same depth pulled slips, casing up to	olaced from (bott had 18" streto o 1150', pum 40', pumped	om), to (top) for each ch, ripped casing sped 15 gel, 50 sa 15 sacks to surfac	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contr	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S	the character of with bailer, p free, pulled on ped 40 sacks Service	same depth pulled slips, casing up to	olaced from (bott had 18" streto o 1150', pum 40', pumped	om), to (top) for each ch, ripped casing aped 15 gel, 50 sa	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contraddress: 401 W Ma	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6	the character of with bailer, p free, pulled on ped 40 sacks Service	same depth pulled slips, casing up to	placed from (bott had 18" streto o 1150', pum 40', pumped	om), to (top) for each ch, ripped casing sped 15 gel, 50 sa 15 sacks to surfac	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contr	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6	the character of with bailer, p free, pulled on ped 40 sacks Service	same depth pulled slips, casing up to	placed from (bott had 18" streto o 1150', pum 40', pumped	om), to (top) for each ch, ripped casing sped 15 gel, 50 sa 15 sacks to surfac	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contraddress: 401 W Ma	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6	the character of with bailer, p free, pulled on ped 40 sacks Service 67554 F. G. Holl C	same depth pulled slips, casing up to s, pulled to 4	placed from (bott had 18" streto o 1150', pum 40', pumped	om), to (top) for each ch, ripped casing sped 15 gel, 50 sa 15 sacks to surfac	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contr Address: 401 W Ma Name of Party Respons State of Kansas	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6	the character of with bailer, p free, pulled on ped 40 sacks Service 67554 F. G. Holl C	same depth pulled slips, casing up to s, pulled to 4	blaced from (botth had 18" stretch of 1150', pum had 10', pumped had black.	om), to (top) for each ch, ripped casing sped 15 gel, 50 sa 15 sacks to surfac License #: 31	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contr Address: 401 W Ma Name of Party Respons State of Kansas Lover	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6 sible for Plugging Fees: Count ness Mipanje	the character of with bailer, purifice, pulled on ped 40 sacks Service 67554 F. G. Holl On Sedgwi	same depth pulled slips, casing up to s, pulled to 4. Company, ck.	blaced from (botth had 18" stretch of 1150', pum had 10', pumped of the L.L.C. , ss (Employee of the series herein contains.	om), to (top) for each ch, ripped casing apped 15 gel, 50 satisfied to surface the control of th	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell 925 or) on above-described well, being fi e above-described well is as filed,
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contr Address: 401 W Ma Name of Party Respons State of Kansas Loven sworn on oath, says: Th	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6 sible for Plugging Fees: Count ness Mipanje	the character of with bailer, purifice, pulled on ped 40 sacks Service 67554 F. G. Holl On Sedgwi	same depth pulled slips, casing up to s, pulled to 4. Company, ck.	blaced from (botth had 18" stretch of 1150', pum had 10', pumped of the L.L.C. , ss (Employee of the series herein contains.	om), to (top) for each ch, ripped casing apped 15 gel, 50 satisfied to surface the control of th	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell 925 or) on above-described well, being fi e above-described well is as filed,
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contr Address: 401 W Ma Name of Party Respons State of Kansas Loven sworn on oath, says: Th	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6 sible for Plugging Fees: Count ness Mipanje	the character of with bailer, purifice, pulled on ped 40 sacks Service 67554 F. G. Holl Content of the facts statement in the facts st	same depth pulled slips, casing up to s, pulled to 4. Company, ck.	blaced from (botth had 18" stretch of 1150', pum had 10', pumped of the L.L.C. , ss (Employee of the series herein contains.	om), to (top) for each ch, ripped casing apped 15 gel, 50 satisfied to surface the control of th	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell 925 or) on above-described well, being fr
hole. If cement or other Sand at 4250', bail ripped casing at 2 pumped 40 sacks, Name of Plugging Contr Address: 401 W Ma Name of Party Respons State of Kansas Loven sworn on oath, says: Th	r plugs were used, state led 4 sacks cement 230', worked pipe pulled to 280', pun ractor: Quality Well S ain, Lyons, KS 6 sible for Plugging Fees: Count ness Mpanje nat I have knowledge of ect, so help me God.	the character of with bailer, purifice, pulled on ped 40 sacks Service 37554 F. G. Holl Organization Sedgwing the facts statement (Signature) (Address)	casing up to a company, cak ents, and matter 9431 E.	L.L.C. (Employee of the control of the control)	om), to (top) for each ch, ripped casing apped 15 gel, 50 satisfied to surface the control of th	plug set. at 2420', worked pipe, acks cement, pulled up to 6 e, pulled joint, backfilled cell 925 or) on above-described well, being fi e above-described well is as filed, ichita, Kansas 67206

Mail to: K66
Notary Public - State of Kansas
BETTY H. SPOTSWOOD
My Appointment Expires 4/30/2010

Mail to: KCC - Conservation Division, 130 S. Market - Room 2078, Wichita, Kansas 67202

RECEIVED

DEC 0 7 2006

KCC WICHITA