

4-070094

5-8

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Number: 15-163-21,914 -00-00
430'FNL & 890'FEL
NE /4 SEC. 31, 09 S, 17 W
4850 feet from S section line
890 feet from E section line

Operator license# 5900

Lease: Schrandt Well # 2 Twin

Operator: Lawbanco Drilling, Inc.

County: Rooks 11S.87

Address: P.O. Box 289
Natoma, Kansas 67651

Well total depth 3565 feet
Conductor Pipe: 0 inch @ 0 sxs.
Surface pipe 8 5/8 Inch @ 163 feet
W/165 sxs.

ABAND. oil well , Gas well _____, Input well _____, SWD. _____, D&A _____

Plugging contractor: Lawbanco Drilling Company License# 5900

Address: P.O. Box 289 - Natoma, Kansas 67651

Company to plug at: Hour: 3:00 A.M. Day: 8 Month: May Year: 1998

Plugging proposal received from: Virgil Dreiling

Company: Lawbanco Drilling Company Phone: 785-885-4676

Were: 8 5/8" set at 163' w/165 sxs common. 4 1/2" set at 3567'w/175 ASC.
W.L. 3560' Fluid Level -0-. Perfs 3420' to 3546'. 61 perforations.
Ordered out 275 sxs 60/40 pozmix - 10% gel with 500# hulls.

Plugging Proposal Received by: Dennis Hamel
Plugging operations attended by agent? All[], Part[], None[]

Completed: Hour: 4:45 P.M., Day: 8, Month: May, Year: 1998

Actual plugging report: Allied pumped 220 sxs 60/40 pozmix - 10% gel with 500# hulls
down 4 1/2" casing. Max. P.S.I. 1000#. S.I.P. 1000#. Hooked up to backside and pressured
up to 600#. (cement in cellar)

Remarks: 01-09-87-Squeezed casing leak at 906'to937'w/250 sxs 60/40 pozmix - 1000#.
Condition of casing(in hole): GOOD BAD _____ Anhy.plug: YES NO _____
Bottom plug(in place): YES , CALC _____ , NO _____ Dakota plug: YES , NO _____
Plugged through TUBING _____ , CASING . Elevation: 2084 GL

I did[] / did not[] observe the plugging.

Richard Williams
(agent)

Form CP-2/30

INVOICED

DATE

MAY 14 1998

INV. NO.

50561

5-13-98