## STATE OF KANSAS STATE CORPORATION COMMISSION

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
211 No. Broadway
Wichite Konese

## WELL PLUGGING RECORD

Wichita, Kansas				v. Sec. 5	4,44	- La /		
NORTH	Location as "N	NE/CNW#SW#"	or footage from	m lines_C_E	「古 Web NW」			
		Lease Owner Okmar Oil Co.						
	Lease Name_	HOL HOL	mes	_ 7 777 7	T T & 3 &	Well No#1		
	Character of V	Woll (completed	n Nation	UST PIGE	y., Wichi	Lta 2, Kansa		
	Date well con		as On, Gas or					
	1	r plugging filed_						
	Application for	r plugging appro	ved			19		
	Plugging comr	nenced	9-2	26 <b>-</b> 62		19		
	Plugging comp	oleted	10-1	1-62		19		
	Reason for aba	indonment of we	ll or producing	formation	The state of the s			
	If a producing	If a producing well is abandoned, date of last production						
	Was permission	Was permission obtained from the Conservation Division or its agents before plugging was co						
Locate well correctly on above Section Plat	menced?							
ne of Conservation Agent who	supervised plugging of th	is well	<u>Eldon P€</u>	<u>tty</u>				
ducing formation		Depth to top	Bottom		. Total Depth o	of Well 317977 Fe		
w depth and thickness of all wa	ater, oil and gas formatio	ns.				0 K		
OIL, CAS OR WATER RECO	ORDS					CASING RECORD		
FORMATION	CONTENT	FROM	то	SIZE	PUT IN	PULLED DUT		
			<u> </u>			,		
						American descriptions and the second		
			<del>                                     </del>					
					AT 1000			
,						Annual Company of the		
Describe in detail the manne introducing it into the hole. If feet for each plus Sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack Capped hole wit	cement or other plugs w g set.  3490 mixed a set pump in p s mud and spot	and ran 4 oulled 2 tted 20 stled rest	sacks c joints p	ement.	th placed, from  lug out.	feet		
Sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack	cement or other plugs w g set.  3490 mixed a set pump in p s mud and spot	and ran 4 oulled 2 tted 20 stled rest	sacks c joints p	ement.  oumped p  ient, pu  - bail	lug out. lled 4 j ed hole	oints, to 30!		
Sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack	cement or other plugs w g set.  3490 mixed a set pump in p s mud and spot	and ran 4 oulled 2 tted 20 stled rest	sacks c joints p	ement.  oumped p  ient, pu  - bail	lug out. lled 4 j ed hole	oints, to 30!		
sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack Capped hole wit	cement or other plugs we get.  3490 mixed a set pump in part and spot as cement, pulling 10 sacks cement.	description is necessing Pulli	sacks of joints packs cem of pipe	same and dep	lug out. lled 4 j ed hole	oints, to 30!		
Sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack Capped hole wit	cement or other plugs wg set.  3490 mixed a set pump in ps mud and spot secment, pulling southwest cas Box 364, Grea pulling co	description is necessing Pullit Bend, F	sacks of joints packs cem of pipe of pipe ary, use BACK of ng Co., ansas	same and dep	lug out. lled 4 j ed hole  continued to the service of the service	oints, to 30'  NOTE OF THE PROPERTY OF THE PRO		
sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack Capped hole wit  e of Plugging Contractor  ess  TE OF Kansas Southwest Casing being first duly sworn on oath	cement or other plugs we get.  3490 mixed a set pump in personal set pum	description is necessing Pullit Bend, F	sacks of joints packs cem of pipe of pipe ary, use BACK of ng Co., ansas	same and dep	lug out. lled 4 j ed hole  continued to the service of the service	oints, to 30!  DIVISION  of the above-describe and the log of the		
sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack Capped hole wit	cement or other plugs we get.  3490 mixed a set pump in personal set pum	description is necessing Pullit Bend, Pullic (e. welches of the forms)	sacks of joints packs cem of pipe of pipe acks cem of pipe of own acts, statement of me God.	same and dep ement.  cumped p ent, pu	lug out. lled 4 j ed hole  contain  servation  wichits  , ss. er or operator) s herein contain	oints, to 30'  NOTE OF THE SEC.		
sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack Capped hole wit  e of Plugging Contractor  ess  TE OF Kansas Southwest Casing being first duly sworn on oath	cement or other plugs we get.  3490' mixed a set pump in personal mud and spotes cement, pulling the loss cement, pulling southwest cas Box 364, Great pulling co., course, says: That I have known at the same are true and continued to the same are true and continued the same are true an	description is necessing Pullit Bend, F	sacks of joints packs cem of pipe of pipe ary, use BACK of ng Co., ansas  Barton mployee of ow acts, statement of me God.	same and dep ement.  cumped p lent, pu ent, pu	lug out. lled 4 j ed hole  continued to the second to the	oints, to 30'  NISCON  OINTS ON  OF the above-describe and the log of the Sec.		
sanded back to Pulled 18 jts, Pumped 25 sacks Spotted 20 sack Capped hole wit  e of Plugging Contractor.  Ess.  E OF Kansas Southwest Casing being first duly sworn on oath c-described well as filed and the	cement or other plugs we get.  3490' mixed a set pump in personal mud and spotes cement, pulling the loss cement, pulling southwest cas Box 364, Great pulling co., course, says: That I have known at the same are true and continued to the same are true and continued the same are true an	description is necessing Pullit Bend, Pulled Pullit Bend,	sacks of joints packs cem of pipe of pipe ary, use BACK of ng Co., ansas  Barton mployee of ow acts, statement of me God.	same and dep ement.  cumped p lent, pu ent, pu	lug out. lled 4 j ed hole  contain  servation  wichits  , ss. er or operator) s herein contain	oints, to 30'  NISCON  OINTS ON  OF the above-describe and the log of the Sec.		

K

15-163-03352-00-6

## DETLUER'S LOG

OPERATOR: FARM NAME: WELL MUMBER:

B - H - P Holmes

LOCATION:

MEG SW/L MW/L

Section 5-98-18W

Rooks County, Kansas

CONTRACTOR:

B - H - P

CASIMO RECORD:

8-5/8" @ 2001

cem. w/125 sacks cement and 1 sack calcium

chloride

BOTARY COMMENCED: ROTARY COMPLETED:

Nov. 23, 1950 Dec. 5, 1950

5-1/2" @ 34911

Cem. w/100 sacks cement

ELEVATION:

2070 Rotary Bushing

INITIAL POTENTIAL:

Anhydrite

## Figures denote bottom of formation

and the same of th	
Shale and Shells	200
Shale	1,00
Shale and Shells	780
Sand and Shale	900
Shale and Shells	1150
Anhydrite	11,90
Red Sed, Shale and Shells	1570
Shale and Shells	2090
Lime and Shale	21.85
Broken Line	2310
Lime	21,95
Broken Line	2585
Limo	2735
Broken Lime	2015
Lime and Shale	3005
Line	31,65
Broken Lime	3491
Arbuckle Lime	<u> </u>
Rotary Total Depth	Mark sough to a serife

TOPS

1450 Kansas City 3243 Conglomerate 3477 Errosional Arbuckle 3485 Arbuckle 31,89

STATE CORPORATION COMMISSION
10/12/62
0CT 12 1962

CONSERVATION DIVISION Wichile, Kanses

STATE OF KANSAS

33

BARTON COUNTY

I hereby certify that the foregoing is, to the best of my knowledge and belief, a full, true and correct drilling log as shown by the daily drilling reports in connection with the aforesaid well.

> Leon F. Huff Leon F. Huff, Partner B - H - P

Subscribed and sworn to before me, the undersigned, a Notary Public, this 8th day of December, 1950.

> Mildred Hobbie Motary Public

My commission expires March 6, 195h.