

4-041760

3-29

API Number: 15-163-01560-00-00

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

NW SW SE /4 SEC. 21, 09 S, 18 W
990 feet from S section line
2310 feet from E section line

Operator license# 5447

Lease: Rempe Well # A-1

Operator: OXY USA, Inc.

County: Rooks

Address: 110 S. Main - #800
Wichita, Kansas 67202

Well total depth 3575 ^{116.18} feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 1496 feet
w/915 sxs.

Aband. oil well X, Gas well, Input well, SWD, D & A

Plugging contractor: Allied Cementing License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: 8:00 A.M. Day: 29 Month: March Year 1996

Plugging proposal received from: Gary Wagner

Company: OXY USA, Inc. Phone:

Were: 5 1/2" casing set at 3570' w/150 sxs cement. Perf. at 3570' - 3575'.
Ordered 425 sxs. 60/40 pozmix -10% gel plus 500# hulls.
Anhy. 1496' - T.O.F. at 1650'. Perf base of S.P. at 1475'.

RECEIVED
KANSAS CORP COMF
APR 12 A 11:19
4-12-96

Plugging Proposal Received by: Dennis L. Hamel

Plugging operations attended by agent? All [X], Part [], None []

Completed: Hour: 10:00 A.M., Day: 29, Month: March, Year: 1996

Actual plugging report: Squeezed 8 5/8" S.P. with 150 sxs 60/40 pozmix - 10% gel with 200# hulls mixed in cement. S.I.P. 100#. Squeezed 5 1/2" casing with 275 sxs 60/40 pozmix 10% gel with 300# hulls mixed in cement. Max. P.S.I. 500#. S.I.P. 400#.

Note: Squeeze S.P. first - Perf base of S.P. at 1475' if you can't pump into it.

Remarks: Allied Cementing.

Condition of casing(in hole): GOOD X BAD
Bottom plug(in place): YES X, CALC, NO
Plugged through TUBING, CASING. Elevation: GL

I did [X] / did not [] observe the plugging.

Dennis L. Hamel
(agent)

Form CP-2/3

INVOICED

DATE 4-16-96

INV. NO. 45303

3-29 JUN 27 1996