

STATE OF KANSAS
STATE CORPORATION
COMMISSION
130 S. Market, Room 2078
Wichita, KS 67202

WELL PLUGGING RECORD
K.A.R. -82-3-117

API NUMBER 15-163-~~95147~~ ⁰¹⁵⁵⁸⁻⁰⁰⁻⁰⁰
LEASE NAME Paradise Creek Unit
WELL NUMBER # 301
2970' Ft. from S Section Line
990' Ft. from E Section Line

TYPE OR PRINT
NOTICE: Fill out completely
and return to
Cons. Div. Office within
30 days

LEASE OPERATOR OXY USA Inc.

SEC 21 TWP 9 RGE 18W E or W

ADDRESS 110 S. Main # 800

COUNTY Rooks

PHONE# (316 265-5624 Operators License 5447

Date Well Completed 08/05/47

Character of Well oil

Plugging Commenced 04/04/96

(Oil, Gas, D&A, SWD, Input, Water Supply Well)

Plugging Completed 04/09/96

The plugging proposal was approved on 04/09/96 (Date)

by Dennis Hamel (KCC District Agent's name).

Is ACO-1 filed? no If not, is well log attached? no

Producing Formation LKC, Arbuckle Depth to Top 3326 Bottom 3585 TD 3585

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
LKC, Arbuckle		3326'	3585'	8 5/8"	1493'	
				5 1/2"	3576'	

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the methods used in introducing it into the hole. If cement or other plug were used, state the character of same and depth placed, from Feet to Feet each set.

See back for details.

RECEIVED
KANSAS CORPORATION COMMISSION
7-3-96
JUL 03 1996
License No.
CONSERVATION DIVISION
WICHITA, KS

(If additional description is necessary, use BACK of this form.)

Name of Plugging Contractor Allied Cementing Co., Inc.

Address 332 W Wichita, Russell, Kansas 67665-0031

NAME OF PARTY RESPONSIBLE FOR PLUGGING FEES: OXY USA Inc

STATE OF Kansas COUNTY OF Sedgwick, ss.

Timothy J. Voss (Employee of Operator) or (Operator) of above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed that the same are true and correct, so help me God.

(Signature) Timothy J. Voss
(Address) 110 S. Main Wichita Kansas 67202

SUBSCRIBED AND SWORN TO before me this 2nd day of July, 1996
Stephen E. Darwin
Notary Public

My commission Expires: 3/9/99

STEPHEN E. DARWIN
NOTARY PUBLIC
STATE OF KANSAS
My Appt. Exp. 3/9/99

07/01/1996

Well Chronological Report

Page 3

PARADISE CREEK UNIT 301

=====

04/23/96 JOB: Plug and Abandon; CMIC: JD HININGER

P&A - Perf. 5 1/2" @ 1475' w/2 holes - cemented down 8 5/8" w/150 sks.
60/40 pozmix containing 10% gel. (Allied) plus 200# hulls - max psi. 0
- shut in 0 psi. - pumped dn 5 1/2" w/275 sks plus 300# hulls - max
psi. 0 - shut in 0 psi. - 4/4/96 - State Wittness - Dennis Hamel -
4/9/96 - Pumped dn 5 1/2" w/75 sks 60/40 pozmix containing 10% gel. and
pumped dn 8 5/8" w/5 sks. - Plugged at 9:00 AM 4/9/96 - State Wittness
Dennis Hamel.

L/E \$ 4747; MAT \$ 1200; CUM: L/E \$ 4747, MAT \$ 1200, TOT \$ 5947;

Geol. 63 500 5-47

WELL RECORD

Company Citizen Service Oil Co. Well No. 1 Farm Hilgers #8*
 Location 330' N and 990' E of 1/4 Corner Sec. 21 T 9 R. 18W
 Elevation 2170 (21680) County Rooks State Kansas
 Drig. Comm. 7-22-47 Contractor R. J. Rine Drilling Co.
 Drig. Comp. 8-5-47 Acid 1500 gallons 8-4-47
 T. D. 3585' Initial Prod. Depthograph Pot: 3000 Oil, 0 wtr, 24 hrs. (8-9-47).

Indicated capacity 3074 bbls.

CASTING & CEMENT:

8-5/8" @ 1493' with 750 sacks cement.
 Cemented top 100' with 150 sacks cement.
 5-1/2" @ 3576' with 150 sacks cement.

Corr. Top Lensing 3318'
 Corr. Top Arbuckle 3575'
 Penetration 10'
 Total Depth 3585'

FORMATION RECORD:

Shale and shells	0-1430
Shale	1482
Anhydrite	1520
Shale and sand	1930
Shale and lime	2095
Lime and shale	2250
Shale and lime	2560
Shale and shells	2770
Shale and lime	2855
Shale and shells	3000
Shale and lime	3255
Lime	3330
Lime and shale	3581
3581 Rotary T.D. = 3579 S.L.M.	
Lime	3585 T.D.

Fill-up

300' oil in 1 hour at 3580'
 550' oil in 1-3/4 hours at 3580
 1600' oil in 4-3/4 hours at 3585'
 1800' oil in 5-3/4 hours at 3585'
 2250' oil in 9-3/4 hours at 3585'
 2400' oil in 11-3/4 hours at 3585'

SLOPE TESTS

250' OK
 500' OK
 750' OK
 1000' OK
 2000' OK
 2500' OK

7-7/8" rotary hole.

RECEIVED
 KANSAS CORP COMM
 1949 MAR 11 A 9:41