## WELL PLUGGING RECORD K.A.R.-82-3-117

15-163-21167-00-00

API NUMBER 163-21167

00 Colorado Derby Ichita, Kamsas 6	7202				LEASE NAME Hinkhouse	
TYPE OR PRI			PRINT	WELL N	UMBER 25	
	NOTICE: Fill out completely and return to Cons. Div.				Ft. from	S Section Line
	office within		•	Ft. from	E Section Line	
ASE OPERATOR	Nadel and Gussma	n		SEC. 2		E. <u>20</u>
DRESS 15 E. 5th, Suite 3200, Tulsa, OK 74103				Rooks		
HONE#(918) 583-3333 OPERATORS LICENSE NO5337				 Date W	ell Complete	<b>d</b> 2/8/81
haracter of Well oil depleted					ng Commenced	4/23/01
	D, Input, Water S	Supply Well)				4/23/01
•	sal was approved					(date)
	Hamel .					
	If not				•	
•	n Arbuckle				tom 3854 T	•D• 3858
• .	ckness of all wa					RECEIV
IL, GAS OR WATER		1		CASING REC	ORD	KANSAS CORPORATION
	Content	From T	o Size		Pulled out	5//7/0 MAY 17
APMETIAN						
				250	None	
• •	Depleted Oil	0 2	258 8 5/8 357 5 1/2	258 3857	None None	CONSERVATION
Arbuckle  . ascribe in detail	Depleted Oil  the manner in without or methods	0 2 0 38 hich the well used in intr	258 8 5/8 5 1/2 I was plus oducing 1	3857 gged, Indica	None ting where tole. If come	CONSERVATION  he mud fluid wa nt or other plug
rbuckle  scribe in detail laced and the me ere used, state looked up annulus and 0/90 poz with 10% ge	Depleted Oil  the manner in wi	0 2 38 hich the well used in introf same and mulus full ceme mped down 5 1/2	258 8 5/8 357 5 1/2  I was plugoducing idepth pent on comple with max property of the control of	gged, Indicatinto the hiaced, frometion. Hooked ress of 800psi	None  ting where to the life t	he mud fluid wa nt or other plug feet each set
escribe in detail laced and the me ere used, state looked up annulus and 50/90 poz with 10% ge	Depleted Oil  the manner in whethod or methods the character press to 400psi. An 1 and 500 # hulls. Pu	o 2 38 hich the well used in introf same and mulus full ceme mped down 5 1/2 Ion is neces	258 8 5/8 357 5 1/2  I was plugoducing I depth pent on comple with max property with	gged, Indicatinto the hiaced, frometion. Hooked ress of 800psi	None  ting where to the life t	conservation  he mud fluid wa  nt or other plug  feet each set  ad mixed 300 sx  300psi.
escribe in detail laced and the me escribe are used, state looked up annulus and 10/90 poz with 10% ge	Depleted Oil  the manner in whethod or methods the character of press to 400psi. And 1 and 500 # hulls. Pu	0 2 0 38  hich the well used in introf same and mulus full ceme mped down 5 1/2  lon is neces  Lied Cementin	258 8 5/8 357 5 1/2  I was plugoducing I depth pent on comple with max property with	gged, Indicatinto the hiaced, frometion. Hooked ress of 800psi	None ting where toole. If come feet toole to say and shut in at says s form.)	conservation  he mud fluid wa  nt or other plug  feet each set  ad mixed 300 sx  300psi.
scribe in detail laced and the me bre used, state looked up annulus and 50/90 poz with 10% ge  (If add ame of Plugging didress P.O.	Depleted Oil  the manner in with the character of the character of the press to 400psi. And 1 and 500 # hulls. Put  ditional descript  Contractor All	o 2 38 hich the well used in introf same and mulus full cememped down 5 1/2 lon is neces Lied Cementin	i was plus oducing i depth p ent on comple with max pr sary, use	gged, indicate into the hilaced, from etion. Hooked ress of 800psi	None ting where toole. If come feet to up 5 1/2 csq. an and shut in at s form.)	conservation  he mud fluid wa  nt or other plug  feet each set  ad mixed 300 sx  300psi.
Arbuckle  escribe in detail laced and the me ere used, state Hooked up annulus and 60/90 poz with 10% ge  (If add ame of Plugging 0 ddress P.O.  AME OF PARTY RESE	Depleted Oil  the manner in whethod or methods the character of press to 400psi. And 1 and 500 # hulls. Put  ditional descript  Contractor All  Box 31, Russell,	o 2 0 38  hich the well used in intr of same and nulus full ceme mped down 5 1/2  lon is neces  Lied Cementin KS 67605  GING FEES:	i was plus oducing i depth p ent on comple with max pr sary, use	gged, Indicate into the hilaced, from etion. Hooked ress of 800psi	None ting where toole. If come feet to up 5 1/2 csq. an and shut in at s form.)	conservation  he mud fluid wa  nt or other plug  feet each set  ad mixed 300 sx  300psi.
laced and the meere used, state Hooked up annulus and 60/90 poz with 10% ge  (If add ame of Plugging of ddress P.O.  AME OF PARTY RESE TATE OF Oklaho M.R. Taylor, M bove-described we tatements, and he same are true	Depleted Oil  the manner in without or methods the character press to 400psi. And 1 and 500 # hulls. Put the contractor All Box 31, Russell,  PONSIBLE FOR PLUGHTMA  Tanager of Product matters herein contracts and correct, so the contract of the contract	o 2 0 38 hich the well used in introf same and mulus full ceme mped down 5 1/2 lon is neces lied Cementin KS 67605 GING FEES: COUNTY OF tion duly sworn of ontained and help me God.	i was plus oducing i depth p ent on comple with max pr sary, use ng  Nadel  Tulsa on oath, s the log (Signat (Addres	gged, indicate into the hiaced, from etion. Hooked ress of 800psi  BACK of this and Gussman  (Employee ays: That I of the above ure)	None  It ing where to look if come in feet to up 5 1/2 csq. and and shut in at standard shut in at standar	conservation  he mud fluid wa nt or other plug feet each set ad mixed 300 sx 300psi.  N/A  or (Operator) of ge of the facts rell as filed tha
Arbuckle  escribe in detail laced and the me ere used, state Hooked up annulus and 50/90 poz with 10% ge  (If add ame of Plugging of ddress P.O.  AME OF PARTY RESE TATE OF Oklaho M.R. Taylor, M bove-described we tatements, and he same are true	Depleted Oil  the manner in without or methods the character press to 400psi. An l and 500 # hulls. Putilitional descript  Contractor All  Box 31, Russell,  PONSIBLE FOR PLUG  ma  Lanager of Product  matters herein cand correct, so	o 2 0 38  hich the well used in introf same and mulus full cememped down 5 1/2  lon is neces Lied Cementin KS 67605  GING FEES: COUNTY OF Lion duly sworn on ontained and help me God.	I was plus oducing is depth pent on comple with max property with	gged, indicate into the hiaced, from etion. Hooked ress of 800psi  BACK of this and Gussman  (Employee ays: That I of the above ure)	None  Iting where to lead of the lead of lead	conservation  he mud fluid wa nt or other plug feet each set ad mixed 300 sx 300psi.  N/A  or (Operator) of ge of the facts rell as filed tha