Notice: Fill out COMPLETELY and return to Conservation Division at the address below within 60 days from plugging date.

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

WELL PLUGGING RECORD K.A.R. 82-3-117

Form CP-4
December 2003
Type or Print on this Form
Form must be Signed
All blanks must be Filled

Address: 250 N. Water, Suite 300					ease Name: Detric								
Phone: (316) 267 - 3241 Operator License #: 30606				v	Vell Number: 5	P2 N2 SW							
Phone: (316) 267 -3241 Operator License #: 30606 Type of Well: EOR COLUMN (Oil, Gas D&A, SWD, ENHR, Water Suprily Well, Cathodic, Other) The plugging proposal was approved on: 2/13/07 (If SWD or ENHR) by: Barry Metz (KCC District Agent's Name)					Spot Location (QQQQ): NE - SW - SE 990 Feet from North / South Section Line 1330 Feet from East / West Section Line Sec. 8 Twp. 15 S. R. 13 East / West								
							Is ACO-1 filed? Yes No If not, is well log attached? Yes No					County: Russell	
							Producing Formation(s): List All (If needed attach another sheet)					Date Well Completed: 1/96	
							LKC Depth to Top: 2935 Bottom: 2948 T.D.					Plugging Commenced: 4/30/07	
	Depth to Top:	Bottom:	T.(D '_	Plugging Completed:	4/30/07							
	Depth to Top:	Bottom:	T.[D	Plugging Completed:								
Show depth and thicknes	ss of all water, oil and gas	formations.				1							
Oil, Gas or Water R ecords					Surface Conductor & Production)								
Formation	Content	From	То	Size	Put In	Pulled Out							
	Surface	Surface	406	10 3/4	406	0							
	Production	Surface	3165	4 1/2	3165	0							
	į	ı											
nole. If cement or other	plugs were used, state the	e character of s	ame depth pla	ced from (bottom)	, to (top) for each plu	r methods used in introducing it into the ug set.							
RU Perf Tech. Per RU Quality Oilwell	r plugs were used, state the	e character of s spf Select-F 500# hulls &	ame depth pla ire gun. Ra 150 sx 60/4	n 50 jts 2 3/8" 0 Poz w/10% g	, to (top) for each plutbg. to 1500'. el @ 1500'. Cem	nent circulated to surface. TOH							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg.	plugs were used, state the of @ 1450' & 750' w/2 Cementing. Pumped &	e character of s spf Select-F 500# hulls & liner. Pump	ame depth pla ire gun. Ra 150 sx 60/4 ed 50 sx 60	n 50 jts 2 3/8" 0 Poz w/10% g	, to (top) for each plutbg. to 1500'. el @ 1500'. Cem 6 gel. Press. to 8	nent circulated to surface. TOH							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs	replugs were used, state the fig. 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2"	e character of s spf Select-F 500# hulls & liner. Pump Plug job wi	ame depth pla ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a	n 50 jts 2 3/8" O Poz w/10% g 0/40 Poz w/10% approved by Ca	, to (top) for each plutbg. to 1500'. el @ 1500'. Cem 6 gel. Press. to 8	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays.							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs	replugs were used, state the rf @ 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" rg & press. to 800 psi.	spf Select-F 500# hulls & liner. Pump Plug job wi	ame depth pla ire gun. Ra 150 sx 60/4 ed 50 sx 60 tnessed & a	n 50 jts 2 3/8" 0 Poz w/10% g 1/40 Poz w/10% approved by Ca	, to (top) for each plutbg. to 1500'. el @ 1500'. Cem 6 gel. Press. to 8 ase Morris w/KC0	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays.							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contraddress: 250 N. Wa	replugs were used, state the fig. 1450' & 750' w/2. Cementing. Pumped & Hooked up to 4 1/2" ag & press. to 800 psi. Pactor: Murfin Drilling Cater, Suite 300;	e character of s spf Select-F 500# hulls & liner. Pump Plug job wi ompany, Inc Wichita,	ame depth pla ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a KS 6720	nced from (bottom) n 50 jts 2 3/8" 0 Poz w/10% g n/40 Poz w/10% approved by Ca	, to (top) for each plutbg. to 1500'. el @ 1500'. Cem 6 gel. Press. to 8 ase Morris w/KC0	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays.							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contraddress: 250 N. Wa	replugs were used, state the rf @ 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" ag & press. to 800 psi. reactor: Murfin Drilling Coater, Suite 300; lible for Plugging Fees: Mi	spf Select-F 500# hulls & liner. Pump Plug job wi ompany, Inc Wichita, urfin Drillin	ame depth pla ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a KS 6720	nced from (bottom) n 50 jts 2 3/8" 0 Poz w/10% g n/40 Poz w/10% approved by Ca	, to (top) for each plutbg. to 1500'. el @ 1500'. Cem 6 gel. Press. to 8 ase Morris w/KC0	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays.							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contr. Address: 250 N. Wa Name of Party Responsi	r plugs were used, state the rf @ 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" g & press. to 800 psi. Pactor: Murfin Drilling Coater, Suite 300; ible for Plugging Fees: Michael County,	e character of s spf Select-F 500# hulls & liner. Pump Plug job wi ompany, Inc Wichita,	ame depth pla ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a KS 6720	nced from (bottom) n 50 jts 2 3/8" 0 Poz w/10% g n/40 Poz w/10% approved by Ca	, to (top) for each plutbg. to 1500'. el @ 1500'. Cem 6 gel. Press. to 8 ase Morris w/KC0	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays.							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contraddress: 250 N. Wa Name of Party Responsi	replugs were used, state the rf @ 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" reg & press. to 800 psi. reactor: Murfin Drilling Cater, Suite 300; rater for Plugging Fees: Michael County, crations Engineer	spf Select-F 500# hulls & liner. Pump Plug job wi ompany, Inc Wichita, urfin Drillin Sedgwick	ame depth pla ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a KS 67202 g Compan	n 50 jts 2 3/8" O Poz w/10% g 0/40 Poz w/10% approved by Ca 2 ny, Inc. (Employee of Op	, to (top) for each plutbg, to 1500'. el @ 1500'. Cem 6 gel. Press. to 8 ase Morris w/KC0 License #: 3060	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays. 06							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contraddress: 250 N. Wa Name of Party Responsi	replugs were used, state the rf @ 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" rg & press. to 800 psi. ractor: Murfin Drilling Cater, Suite 300; ible for Plugging Fees: Mirations Engineer at I have knowledge of the	spf Select-F 500# hulls & liner. Pump Plug job wi ompany, Inc Wichita, urfin Drillin Sedgwick	ame depth pla ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a KS 67202 g Compan	n 50 jts 2 3/8" O Poz w/10% g 0/40 Poz w/10% approved by Ca 2 ny, Inc. (Employee of Op	, to (top) for each plutbg, to 1500'. el @ 1500'. Cem 6 gel. Press. to 8 ase Morris w/KC0 License #: 3060	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays.							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contr. Address: 250 N. Wa Name of Party Responsionate of Etate of Kansas Susan Sears, Oper sworn on oath, says: The same are true and correct	replugs were used, state that (a) 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" g & press. to 800 psi. actor: Murfin Drilling Coater, Suite 300; ible for Plugging Fees: Minations Engineer at I have knowledge of the ct, so help me God.	spf Select-F 500# hulls & liner. Pump Plug job wi ompany, Inc Wichita, urfin Drillin Sedgwick facts statemen (Signature)	ame depth pla ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a KS 6720 g Compan	nced from (bottom) n 50 jts 2 3/8" 0 Poz w/10% g n/40 Poz w/10% approved by Ca ny, Inc. (Employee of Ops herein contained)	, to (top) for each plutbg, to 1500'. el @ 1500'. Cem 6 gel. Press. to 8 ase Morris w/KC0 License #: 3060	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays. 06							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contraddress: 250 N. Waller Waller Waller State of Kansas Susan Sears, Oper sworn on oath, says: The same are true and correct	replugs were used, state that (a) 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" g & press. to 800 psi. actor: Murfin Drilling C atter, Suite 300; ible for Plugging Fees: Mi County, arations Engineer at I have knowledge of the ct, so help me God.	e character of s spf Select-F 500# hulls & liner. Pump Plug job wi company, Inc Wichita, urfin Drillin Sedgwick facts statemen (Signature) (Address) 256	ame depth place ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a company is, and matters on N. Water,	n 50 jts 2 3/8" 0 Poz w/10% g 1/40 Poz w/10% approved by Ca 2 ny, Inc. (Employee of Ops herein contained) Suite 300; Wide	to (top) for each plutbg. to 1500'. el @ 1500'. Cem gel. Press. to 8 ase Morris w/KC0 License #: 3060 erator) or (Operator) and the log of the acceptance of	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays. 06 on above-described well, being first duly above-described well is as filed, and the							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contr. Address: 250 N. Wa Name of Party Responsi State of Kansas Susan Sears, Oper sworn on oath, says: The same are true and correct	replugs were used, state that (a) 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" g & press. to 800 psi. actor: Murfin Drilling Coater, Suite 300; ible for Plugging Fees: Minerations Engineer at I have knowledge of the ct, so help me God.	e character of s spf Select-F 500# hulls & liner. Pump Plug job wi company, Inc Wichita, urfin Drillin Sedgwick facts statemen (Signature) (Address) 256	ame depth place ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a company is, and matters on N. Water,	nced from (bottom) n 50 jts 2 3/8" 0 Poz w/10% g n/40 Poz w/10% approved by Ca approved by Ca ca ca ca ca ca ca ca ca ca	to (top) for each plutbg. to 1500'. el @ 1500'. Cem gel. Press. to 8 ase Morris w/KCC License #: 3060 erator) or (Operator) and the log of the achita, KS 67202	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays. 06							
RU Perf Tech. Per RU Quality Oilwell w/50 jts 2 3/8" tbg. Hooked-up to 6" cs Name of Plugging Contraddress: 250 N. Waller Waller Waller State of Kansas Susan Sears, Oper sworn on oath, says: The same are true and correct	replugs were used, state that (a) 1450' & 750' w/2 Cementing. Pumped & Hooked up to 4 1/2" g & press. to 800 psi. actor: Murfin Drilling C atter, Suite 300; ible for Plugging Fees: Mi County, arations Engineer at I have knowledge of the ct, so help me God.	e character of s spf Select-F 500# hulls & liner. Pump Plug job wi company, Inc Wichita, urfin Drillin Sedgwick facts statemen (Signature) (Address) 256	ame depth place ire gun. Ra 150 sx 60/40 ed 50 sx 60 tnessed & a company is, and matters on. Water, ore me this 150 km.	nced from (bottom) n 50 jts 2 3/8" 0 Poz w/10% g n/40 Poz w/10% approved by Ca approved by Ca ca ca ca ca ca ca ca ca ca	to (top) for each plutbg. to 1500'. el @ 1500'. Cem gel. Press. to 8 ase Morris w/KC0 License #: 3060 erator) or (Operator) and the log of the acceptance of	nent circulated to surface. TOH 00 psi. SI w/400 psi. C, Hays. 06 on above-described well, being first duly above-described well is as filed, and the							

MAY 2 5 2007

CONSERVATION DIVISION VICUITA KR